

**Industrial performance and durability.**

Anti-slip ribs on motor housing for higher maneuverability and better control.



**Toggle switch**

**Vent slots designed to direct the exhaust air stream towards the opposite side of user.**

**Stepped neck of solid aluminum barrel**

Following optional accessories can be attached to the neck;

- 1) Vise holder at the 35mm diameter portion of the neck
- 2) Drill stand at the 43mm diameter portion of the neck
- 3) Side handle at the 43mm diameter portion of the neck

**Round-Shaped Collet Nut**


Reduces the possibility of damage/ scratches to workpiece compared with the conventional hex-type collet cones.

**No load speed  
33,000 rpm**



**Anti-slip rubber cover is available.**



 **Double Insulation**

<b>Continuous rating Input</b>	480W
<b>Capacity</b>	Collet : 6mm or 1/4"
<b>Wheel diameter</b>	20mm (13/16")
<b>No load speed (rpm)</b>	33,000
<b>Dimensions (L x W x H)</b>	350x75x75mm (13-3/4"x2-15/16"x2-15/16")
<b>Net Weight*</b>	1.4kg (3.1lbs)
<b>Power supply cord</b>	2.0m (6.6ft)

**411** 

**Standard Equipment :** Wrench (2pcs.)  
(Tool does not come with wheel point.)