

Cordless Impact Wrench DTW300 1/2" (12.7 mm) DTW302 3/8" (9.5 mm)



BL XPT

Lightweight and easy to handle



High Torque

Max Fastening Torque

330 / 300 N·m


C ring

DTW300 1/2" (12.7 mm) **DTW302** 3/8" (9.5 mm)



Changing the application mode

This tool employs several easy-to-use application modes for driving bolts with good control.




Twin LED job light

with preglow and afterglow functions





Pushing a button Max mode Hard mode **Medium mode** Soft mode

















18V	DC18RD	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 _{min}	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Impact Wrench

DTW300 1/2" (12.7 mm) **DTW302** 3/8" (9.5 mm)

Fastening Capacities Standard Bolt: High Strength Bolt: Wariable Speed Brake Square Drive Reversing Electronic 4-Speed Vibration Level -
→- Built-in Job Light Carrying Case

Max Fastening Torque Sound Pressure Level Sound Power Level Dimensions (L x W x H)

M10 - M20 (3/8" - 3/4") M10 - M16 (3/8" - 5/8") 12.7 mm (1/2") No Load Speed (RPM) 0-3,200/0-2,600/0-1,800/0-1,000 Impacts Per Minute (IPM) 0-4,000/0-3,400/0-2,600/0-1,800

0-3,200/0-2,600/0-1,800/0-1,000 330 N·m (240 ft.lbs.) 12.5m/s 97 dB(A) 108 dB (A) w/BL1815N/BL1820B:144x81x228 mm w/BL1830B/BL1840B/BL1850B/BL1860B: 144x81x246 mm

Net weight 1.5 - 1.8 kg (3.4 - 4.1 lbs.) 1.4 - 1.8 kg (3.1 - 4.0 lbs.) DTW300FIX4:2 battery 3.0Ah(BL1830B), fast charger (DC18RC), impact socket case(B-66232), DTW302RTJ: 2 battery 5.0Ah(BL1850B), 1/2 SQ. DR. extension (B-66248), (Connector plastic case type 2(821550-0))
DTW300RTJ: 2 battery 5.0Ah(BL1850B), fast charger (DC18RC) (Connector plastic case type 2(821550-0)) DTW300Z: Battery & charger are sold seperately

DTW300

DTW302 M10 - M20 (3/8" - 3/4") M10 - M16 (3/8" - 5/8") 9.5 mm (3/8") 0-3,200/0-2,600/0-1,800/0-1,000 0-4,000/0-3,400/0-2,600/0-1,800 300 N·m (220 ft.lbs.) 15.4m/s² 94 dB(A) 105 dB (A) w/BL1815N/BL1820B: 138x81x228 mm w/BL1830B/BL1840B/BL1850B/BL1860B: 138x81x246 mm

fast charger (DC18RC), (Connector plastic case type 2(821550-0)) DTW302Z: Battery & charger are sold seperately

Standard Equipment :

(346317-0), tool hanger

set (197941-0), hand strap

(163400-6)(DTW302 only)

(+) Truss head screw M4X12 (266622-8), hook

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

CÔNG TY TNHH MAKITA VIÊT NAM KID 456, Block 16, 181.12 Didding of 3, KIN VSP B, P. Hoa Phin, TP. Thiu Dais Midt, Blinh Duding. ### OFFICE OF A SEC 2833 - Fax (0274 SEC 2833) - Website: www.makita.com.um

CHI NHÁNH CẦN THƠ

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

CHÍ NHÁNH BUÔN MA THUỘT 68 Lẻ Đức Thọ, P. Tháng lợi, TP. Buôn Ma Thu

CHI NHÁNH NHA TRANG Ló 3638 đượng Bộ, Khu đó thị Vinh Điềm Trung, Xã Vinh Ngọc TP. Nha Trang, T. Khánh Hòa DT: 0258 220 0039 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH Số 12 Trinh Văn Cần, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh. ĐT: 0283 821 5191