



Cordless Cleaner CL104D / CL104DX, CL105D / CL105DX

20W High suction power in Turbo mode

Turbo mode is available by pressing and holding down Touch button switch.

CL104D
CL105D

CL104DX
CL105DX

Powered by
10.8V built-in
Li-ion battery



Turbo mode* (Long press)

- Turbo mode* is available by pressing and holding down Touch button switch.
- High/ Low suction mode is also available as well as CL series.
- * Features highest suction

High suction power
20W
in Turbo mode*

* Features the highest suction of the 3 power modes and is available by pressing and holding down Touch button switch

Sash Nozzle





Model: CL104D

Model: CL104DX

T-nozzle with enhanced maneuverability

- Ingenious swivel joint always keeps the vacuum head as close to the floor surface as possible even when cleaning tight places such as beneath sofas.
- Dust accumulation on and around the roller is greatly reduced by the following improvements:
 - longer distance between the wiper and each roller
 - larger opening around each roller
 - fixed roller shaft
 - reduced floor contact area of the roller



Powered by 10.8V/1.5Ah built-in Li-ion battery CL104D/X

Powered by 10.8V/1.3Ah built-in Li-ion battery CL105D/X

LED lamp for two warnings

1. Battery capacity warning lamp
2. Battery charge lamp turns off to indicate the battery is fully charged; a microcomputer detects full charge of the battery and turns off the lamp.

Front cover easier to open/ close

- Simply by pushing a button, you can open the front cover for easy dust bag change.
- You do not have to worry about where to put removed front cover because it is hinged to the housing.



Angled suction port

- Allows for easy floor cleaning without T-nozzle.
- Prevents extension pipe from wobbling in use.



Cordless Cleaner

CL104D / CL104DX, CL105D / CL105DX

Capacity	500mL
Max. air flow	1.1m ³ /min
Continuous use (minutes)	10 (Turbo), 15 (High), 30 (Low) CL104D / CL104DX 7 (Turbo), 10 (High), 20 (Low) CL105D / CL105DX
Max. sealed suction (water column)	3.3kPa (340mmH ₂ O)
Dimensions (L x W x H)	446x113x136mm (17-1/2"x4-7/16"x5-3/8")
Net weight*	1.1kg (2.3lbs)

Electronic 3-Speed

Soft Start

Standard Equipment :

Charger DC1001 (Charging time: 180 min. [approx]), Nozzle Assembly, Sash Nozzle, Sash Nozzle Holder, Pipe, Cloth Dust Bag, Paper Dust Bag

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-AD