



Cordless Driver Drill
DF347D 10mm (3/8") / DF457D 13mm (1/2")

Satisfy Professional's Needs

Cordless Hammer Driver Drill
HP347D 10mm (3/8") / HP457D 13mm (1/2")



14.4V
DF347D

18V
DF457D

14.4V
HP347D

18V
HP457D

LIGHTER

1.1Ah Lithium-ion Series

All metal gear construction for extra high transmission durability

Gear case

covers gears completely for increased durability against dust.

Torque setting :
16 stage + drill mode



Mechanical 2-speed gearing

- High speed mode for speedy drilling in light duty applications
- Low speed mode for heavy duty applications requiring high torque

14.4V Li-ion

Battery For Model:
DF347D, HP347D



BL1411G 1.1Ah

18V Li-ion

Battery For Model:
DF457D, HP457D



BL1811G 1.1Ah

Charger : DC18WA

Charging Time
60 min.



Single sleeve keyless chuck

allows for easy bit installation/removal with one hand.

Push button type reverse switch

Variable speed control by trigger

Rubberized soft grip

provides more control and reduced fatigue.



DF347D



DF457D



HP347D

Cordless Driver Drill / Cordless Hammer Driver Drill

DF347D / DF457D / HP347D / HP457D

- Variable Speed
- Electric Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 16
- Carrying Case



Driver Drill
DF347D **14.4V Li-ion**



Driver Drill
DF457D **18V Li-ion**



Hammer Driver Drill
HP347D **14.4V Li-ion**



Hammer Driver Drill
HP457D **18V Li-ion**

	DF347D	DF457D	HP347D	HP457D
Capacity	Steel : 10mm (3/8") Wood : 25mm (1")	Steel : 13mm (1/2") Wood : 36mm (1-7/16")	Steel : 10mm (3/8") Wood : 25mm (1") Masonry : 10mm (3/8")	Steel : 13mm (1/2") Wood : 36mm (1-7/16") Masonry : 13mm (1/2")
Impacts per minute (ipm)	-	-	Hi : 0-21,000 Lo : 0-6,000	Hi : 0-21,000 Lo : 0-6,000
No load speed (rpm)	Hi : 0-1,400 Lo : 0-400	Hi : 0-1,400 Lo : 0-400	Hi : 0-1,400 Lo : 0-400	Hi : 0-1,400 Lo : 0-400
Max. fastening torque	Hard / Soft : 30 / 15N.m	Hard / Soft : 42 / 24N.m	Hard / Soft : 30 / 15N.m	Hard / Soft : 42 / 24N.m
Dimensions (L x W x H)	198x83x235mm (7-3/4"x3-1/4"x9-1/4")	221x83x240mm (8-3/4"x3-1/4"x9-1/2")	216x83x235mm (8-1/2"x3-1/4"x9-1/4")	239x83x240mm (9-3/8"x3-1/4"x9-1/2")
Net weight*	1.4kg (3.2lbs)	1.7kg (3.7lbs)	1.5kg (3.3lbs)	1.7kg (3.8lbs)

Standard Equipment : Charger, Battery Cartridge, (+) (-) Bit

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BB-AD