Best possible ergonomic handle for driver-drill applications



Cordless Driver Drill		DDF481 13mm (1/2")		
			DHP481	DDF481
Variable Speed	Carrying Case	Capacity	Steel : 13mm (1/2")	Steel : 13mm (1/2")
			Wood : 76mm (3")	Wood : 76mm (3")
Me Brake			Masonry : 16mm (5/8")	-
		Impacts per minute (ipm)	Hi:0-31,500	-
Reversing			Lo:0-8,250	-
		No load speed (rpm)	Hi:0-2,100	Hi : 0-2,100
Mechanical 2-Speed			Lo:0-550	Lo:0-550
		Max. fastening torque	Hard / Soft : 115 / 60N.m	Hard / Soft : 115 / 60N.m
Keyless Chuck		Dimensions (L x W x H)	205x79x249mm (8-1/8"x3-1/8"x9-3/4")	205x79x249mm (8-1/8"x3-1/8"x9-3/4")
	-70	Net weight*	2.4kg (5.2bs) with BL1815N	2.4kg (5.2lbs) with BL1815N
200	5000	-	2.7kg (5.9lbs) with BL1830, BL1840	2.6kg (5.8lbs) with BL1830, BL1840
Torque Setting 21				
	<u> </u>	Standard Equipment :		
		Fast Charger, Battery Cartridge, (+) (-) Bit x2, Bit Holder, Grip Assembly, Depth Gauge (DHP481 only)		

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-AC



Max lock torque*: 125N.m.

Cordless Driver Drill DDF481


Cordless Hammer Driver Drill DHP481



* with 4.0Ah Battery (BL1840)

Photo: DHP481

Tool does not come with bit.



Cordless Hammer Driver Drill Cordless Driver Drill







Max lock torque: 125 N.m (1,090 in.lbs)

Efficient Brushless DC motor provides higher power and productivity.

45%* increase in work efficiency compared with predecessor model





Compact overall length: 205mm for increased maneuverability

20mm compact than our predecessor model



More work amount than predecessor model on a single full battery charge because of no friction loss caused by brushes

Test conditions: Drilled in a brick to a depth of 30mm with ø8mm

DHP481 (High Speed, 4.0Ah Battery)



predecessor model (High Speed, 3.0Ah Battery)





