

# Aluminum gear housing and all metal gear construction

for extra-high transmission durability



**Compact overall length**  
DDF484: 172mm, DHP484: 182mm

**21 Torque settings**



**Mechanical 2-speed gearing**



**Single sleeve keyless chuck**

allows for easy bit installation/removal by one hand.

**Capacity of drill chuck**

1.5mm (1/16") - 13mm (1/2")

**Twin LED job light with preglow and afterglow functions**



**Variable speed control by trigger**

**Best possible ergonomic handle with soft grip for driver-drill applications**

- In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.
- Newly designed slimmer grip provides comfortable grip with less fatigue.

**Powered by the following 18V Li-ion batteries**

with Battery fuel gauge



\*without Battery fuel gauge



- BL1860B (6.0Ah)
- BL1850B (5.0Ah)
- BL1840B (4.0Ah)
- BL1830B (3.0Ah)
- BL1820B (2.0Ah)
- \*BL1815N (1.5Ah)

Fast charger  
DC18RC



Charger  
DC18SD



**Belt clip**

**Cordless Hammer Driver Drill  
DHP484**



**Cordless Driver Drill  
DDF484**



| Cordless Driver Drill        | DDF484 13mm(1/2") |
|------------------------------|-------------------|
| Cordless Hammer Driver Drill | DHP484 13mm(1/2") |

|                               | DDF484   | DHP484  |
|-------------------------------|--|---|
| <b>Capacity</b>               | Steel : 13mm (1/2 ")<br>Wood : 38mm (1-1/2")                 | Steel : 13mm (1/2 ")<br>Wood : 38mm (1-1/2")<br>Masonry : 13mm (1/2") |
| <b>Impacts per minute</b>     | -  | Hi : 0 - 30,000 Lo : 0 - 7,500  |
| <b>No load speed (rpm)</b>    | Hi : 0 - 2,000 Lo : 0 - 500                                  | Hi : 0 - 2,000 Lo : 0 - 500   |
| <b>Max. fastening torque</b>  | Hard / Soft : 54 / 30N·m                                     | Hard / Soft : 54 / 30N·m  |
| <b>Dimensions (L x W x H)</b> | 172x79x244mm (with BL1815N)<br>(6-3/4"x3-1/8"x9-5/8")        | 182x79x244mm (with BL1815N)<br>(7-1/8"x3-1/8"x9-5/8")                 |
|                               | 172x79x261mm (with BL1860B)<br>(6-3/4"x3-1/8"x10-1/4")       | 182x79x261mm (with BL1860B)<br>(7-1/8"x3-1/8"x10-1/4")                |
| <b>Net Weight</b>             | 1.5kg (3.4lbs)(with BL1815N)<br>1.8kg (3.9lbs)(with BL1860B) | 1.6kg (3.5lbs)(with BL1815N)<br>1.8kg (4.0lbs)(with BL1860B)          |

**Standard Equipment :** Belt Clip, (+)(-) bit, Battery, Charger

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 21
- Built-in Job Light
- Carrying Case

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201608



# Cordless Driver Drill

DDF484

# Cordless Hammer Driver Drill

DHP484



## Durable Aluminum gear housing



Cordless Driver Drill  
DDF484



Cordless Hammer  
Driver Drill  
DHP484



High speed  
**2,000**rpm

Predecessor model: 1,550rpm

Compact overall length  
**182**mm (DHP484)

Predecessor model: 199mm