

# **Cordless Hammer Driver Drill** Cordless Driver Drill DHP487 / DDF487 13 mm (1/2")





**Max Lock Torque** 

**Light weight** 

Battery: BL1820B / Model: DDF487





## **Compact and Slim design**

### **Compact**






**Ergonomic handle for screwing applications** 



In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.

Ribbed soft grip enables all finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation.



Robustness is highlighted by the aluminum diecast cover added around the gear housing case.



Twin LED job light



with preglow and afterglow functions

#### Variable speed control trigger



**Mechanical 2-speed** gearing



Steel / Wood (Auger Bit / Self-Feed Bit / Hole Saw): 13 / 36 / 35 / 51 mm

150 x 81 x 248 mm w/ BL1830B / BL1840B / BL1850B / BL1860B:

High / Low: 0 - 1,700 / 0 - 500 Hard / Soft: 40 / 25 N·m

w/ BL1815N / BL1820B:

150 x 81 x 232 mm

1.3 - 1.6 kg

Drilling into Metal:  $2.5 \text{ m/s}^2$  or less 73 dB(A)

#### **Accessories** Phu kiên đi kèm

#### Hook

For BL1815N / BL1820B Part No. 346449-3

For BI 1830B / BI 1840B / BI 1850B / BI 1860B Part No. 346317-0



photo: DHP487

#### Bit holder

Part No. 452947-8





## **Cordless Hammer Driver Drill**

Cordless Driver Drill

Wariable Speed Marake Brake

Reversing

Mechanical 2-Speed

Keyless Chuck Torque Setting 20

-
→- Built-in Job Light

Carrying Case Standard Equipment:

Hook (346317-0), bit holder (452947-8), +- BIT 2-45 (784637-8), handstrap (163400-6)

Capacity Chuck Capacity Impacts Per Minute (IPM) No Load Speed (RPM) Max Fastening Torque Max Lock Torque Vibration Level

Sound Pressure Level Sound Power Level Dimensions (L x W x H)

DHP487 13 mm (1/2")

**DDF487** 13 mm (1/2")

**DHP487** Steel / Wood (Auger Bit / Self-Feed Bit / Hole Saw) / Masonry: 13 / 36 / 35 / 51 / 13 mm

1.5 - 13 mm High / Low: 0 - 25,500 / 0 - 7,500 High / Low: 0 - 1,700 / 0 - 500 Hard / Soft: 40 / 25 N·m

40 N·m Impact Drilling into Concrete: 10.5 m/s<sup>2</sup> Drilling into Metal: 2.5 m/s<sup>2</sup> or less 83 dB(A)

w/ BL1815N / BL1820B: 164 x 81 x 232 mm w/ BL1830B / BL1840B / BL1850B / BL1860B: 164 x 81 x 248 mm 1.4 - 1.7 kg

94 dB(A)

DHP487Z/DDF487Z: No battery, charger
DHP487RFJ/DDF487RFJ: 1 DC18RC fast charger, 2 battery BL1830B set, connector plastic case (Type2)(821550-0)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Net weight

### CÔNG TY TNHH MAKITA VIỆT NAM (810 456) Block 16, 1811/2 Duding số 3, MCN VSP 4, P, Hoa Phin, TP, Thid Dâu Một, Binh Duding 617, 0274 382 8338 - Fax: 0274 382 8338 - Website: www.makita.com.wn

CHÍ NHÁNH CTY TNHH MAKÍTA VN TAI MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG Kho 5, Số 1, Đường Số 6, KCN - ĐT - DV VSIP Bắc Ninh, X. Phú Chắn TP. Từ Sơn, T. Bắc Ninh. ĐT: 0222 376 5942 Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI 65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội. 9T: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ i Văn Kiệt, Khu Vực 5. P. An Thời, Q. Bình Thủy,

CHÍ NHÁNH BUÔN MA THUỘT 68 Lẻ Đức Thọ, P. Tháng lợi, TP. Buôn Ma Thu TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG
Li 36-38 dường BB, Khu độ thị Vĩnh Điểm Trung, Xã Vĩnh Ngọc, TP. Nha Trang, T. Khánh Hòa

1.5 - 13 mm

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH Số 12 Trinh Văn Cần, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh. ĐT: 0283 821 5191