



1.6mm (16Ga)
Cordless Nibbler
DJN161

Satisfy Professional's Needs



**Cordless provides
smooth operation**

Excellent performance as powerful as AC model

Easy-to-operate slide-type on/off switch with lock-on function

Grooves in die holder serve as thickness gauge for allowable cutting thickness:
1.2mm (18Ga.)
1.6mm (16Ga.)

Die holder swivels a full 360 according to shape of material and cutting direction, and is positively locked at 90 each.

Notch in die holder indicates the cutting line on material.

Chip Disposal: Chips fall below, not remaining on material, where they can cause rust. No burrs on surface.

Externally accessible carbon brush

Easy-to-grip motor housing

- Small circumference for easy handling
- Rubberized soft grip for more comfort and better control with minimized hand fatigue and pain.

Battery capacity warning lamp

When remaining battery capacity decreases below a certain limit, the motor automatically stops and solid red light reminds you to replace battery.

Anti-restart function for safety (with warning lamp)

The motor does not start up if battery is inserted with the switch locked on. In this case, the lamp starts blinking slowly, indicating that the Anti-restart function is on; and can be turned off by sliding the switch to the off position.

Warning lamp

Battery



BL1830:
18V 3.0Ah

Charger

DC18RC / DC18RA
Charging time
22minutes

Fast Charging
22 min

DC18SD
Charging time
60minutes



High cutting capacity

up to **1.6mm (16Ga)** thick mild steel

up to **1.2mm (18Ga)** thick stainless steel

up to **2.5mm (12Ga)** thick aluminum

Punch

Part No. A-83951



Die

Part No. A-15051



Cordless Nibbler

DJN161Z

1.6mm (16Ga)

DJN161Z	
Capacity	Steel up to 400 N/mm ² : 1.6mm (16Ga) Steel up to 600 N/mm ² : 1.2mm (18Ga) Aluminum up to 200 N/mm ² : 2.5mm (12Ga)
Min. cutting radius	Outside edge: 50mm (2") Inside edge: 45mm (1-3/4")
Strokes per minute (spm)	1,900
Dimensions (L x W x H)	313x78x189mm
Net Weight*	2.2kg with BL1830 DJN161Z: No battery, charger
Standard Equipment: Punch (A-83951), die (A-15051), wrench 32 (781028-4), hex. wrench 2.5 (783208-8).	

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 18L1-2 Đường số 3, KCN VSIP II, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho 5, số 1, đường số 6, KCN - ĐT - DV VSIP Bắc Ninh, X. Phù Chấn, T.X. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG

102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079/ 0236 352 5179 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

366 Võ Văn Kiệt, Khu Vực 5, Phường An Thới, Quận Bình Thủy, Thành Phố Cần Thơ
ĐT: 0292 3894 358 Fax: 0292 3894 359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUỒN MA THUỘT

60 Y Jút, P. Thống Nhất, TP. Buon Ma Thuột, T. Đắk Lắk
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

Số 15, Phố Phạm Hồng Thái, Q. Hồng Bàng, TP. Hải Phòng
Điện thoại: 0225 8831 529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG

1053 Đường 2 tháng 4, P. Vạn Thạnh, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 3823 338

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
Điện thoại: 028 3821 5191