



Job Site Speaker
DMR203 12V max-18V / AC



Powerful & Deep Stereo Sound

Wireless Stereo Pairing

Left

Right



Multi-speaker connection

True Wireless Stereo

True Wireless Stereo (TWS) technology allows to wirelessly pair two DMR203's via Bluetooth multi-pairing and to enjoy a deep, rich and powerful stereo sound.




Group chain

Up to ten DMR203's can be paired and connected to one mobile device to play the same sound simultaneously.



7 Selectable sound modes

- Sound mode can be selected to suit the music genre.
- MY EQ (my equalizer) mode enables to individually adjust treble, midrange and bass for a desired sound quality.



Equalizer
FLAT / JAZZ / ROCK / CLASSIC / POP / NEWS / MY EQ

Dust and water resistance (only with DC power)


IP65

For use in outdoor applications or harsh environments



Color LCD panel

- displays the status of speaker and equalizer settings.
- displays song titles and artist names, etc.



2 way high quality speaker

Woofer : Ø 101.6mm, for low sound
Tweeter : Ø 36mm, for high sound



Connection

Bluetooth



AUX-IN jack



USB output terminal for charging smartphone etc.



Storage box for portable devices
Mobile device can be charged while stored.



Power source

Li-ion battery (slide type)
12Vmax **18V**



AC



Continuous run time (approx): hour

On a single full battery charge

| 12V max | Bluetooth | AUX IN | 18V | Bluetooth | AUX IN |
|-----------------|-----------|--------|----------------|-----------|--------|
| BL1016 (1.5Ah) | 8.5 | 9.5 | BL1815N(1.5Ah) | 7.5 | 8.5 |
| | | | BL1820B(2.0Ah) | 10 | 11 |
| BL1021B (2.0Ah) | 11 | 12 | BL1830B(3.0Ah) | 14 | 16 |
| | | | BL1840B(4.0Ah) | 20 | 22 |
| BL1041B (4.0Ah) | 22 | 25 | BL1850B(5.0Ah) | 26 | 29 |
| | | | BL1860B(6.0Ah) | 32 | 35 |

Job Site Speaker

DMR203 12V max-18 V / AC

| | |
|-------------------------------|--|
| Speaker Size | Woofer/Tweeter: Ø101.6 / Ø36 mm |
| Max Output | 18V / 12Vmax / AC : 10 / 3.5 / 3.5 W |
| Bluetooth | Version: 5.0 Profile: A2DP / SCMS-T / AVRCP Supported Codec: SBC Max Transmission Range (Optimum): 10 m (33 ft) Max Transmission Range (Possible): 30 m (100 ft) |
| Dimensions (L x W x H) | w/ Handle in Retracted Position: 217x206x199 mm (8-1/2"x8-1/8"x7-7/8") w/ Handle in Upright Position: 217x206x285 mm (8-1/2"x8-1/8"x11-1/4") |
| Net weight | 2.7 - 3.4 kg (6.0 - 7.5 lbs.) |

Standard Equipment: AC Adapter

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201912