

# Easy-to-Customize

## Trimmer base assembly with Square base plate



Convenient for cutting workpiece using guide rule, auxiliary wood fence

## Offset base plate with Grip assembly



Convenient for cutting wide workpiece

## Plunge base assembly with Side grip



Convenient for cutting while holding weight on one of the two handles of the base

## Trimmer base with Grip attachment set



Convenient for trimming while holding two handles of the Trimmer base

## Trimmer base assembly with Straight guide



Straight guide Part No. 122391-0

## Trimmer base assembly with Trimmer guide assembly



Trimmer guide assembly Part No. 122703-7

## Plunge base assembly with Guide rail adapter set, Guide rail & Clamp set



Guide rail adapter set Part No. 194579-2

Guide rail length Part No. 1.4m 194368-5 1.9m 194925-9 3.0m 194367-7

Clamp set Part No. 194385-5

## Collet cone

Size	Part No.
8mm	763618-5
3/8"	763619-3
6mm	763636-3
1/4"	763637-1

## Base plate

	Part No.
Trimmer base plate	454842-8
Plunge base plate	450819-1
Tilt base plate	413150-6
Offset base plate	413148-3

## Plunge base assembly with Straight guide & Dust nozzle



Dust nozzle Part No. 194733-8

Guide holder set Part No. 195564-8


Straight guide (with auxiliary wood) Part No. 122391-0

Straight guide with micro adjustment (Alumi w/o mark of origin) Part No. 195136-9

Straight guide Part No. 164834-6

## Templet guide

### for Trimmer base



A(mm)	B(mm)	C(mm)	Part No.
for Trimmer base			
8	10	9.5	343577-5
for Plunge base			
7.7	9.5	11.5	164379-4
9	11	13	164775-6
10	12	9	164388-3
11	12.7	13	164776-4
14	17	20	165366-6
14.5	16	13	193043-0
18	20	13	164393-0
22	24	13	165364-0
24	27	13	164470-8
25	29	15	163080-8
27	30	13	164471-6
37	40	13	165046-4
37	40	13	164472-4

## Cordless Trimmer DRT50Z 6 mm, 8 mm

Variable Speed	<b>No Load Speed (RPM)</b> 10,000 - 30,000
Constant Speed	<b>Plunge Capacity</b> with Trimmer Base: 0 - 40 mm with Plunge Base: 0 - 35 mm
Soft Start	<b>Vibration Level</b> Rotation without Load: 2.5 m/s <sup>2</sup> or less Cutting Grooves in MDF: 4.5 m/s <sup>2</sup>
Dust Collection	<b>Sound Pressure Level</b> 78 dB(A)
Built-in Job Light	<b>Dimensions (L x W x H)</b> with BL1815N / BL1820B: 134x89x208 mm with BL1830B / BL1840B / BL1850B / BL1860B: 134x89x226 mm
Carrying Case	<b>Net weight</b> 1.8 - 2.1 kg (3.9 - 4.6 lbs.)

**DRT50Z:** Battery & charger not include

**Standard Equipment:** Collet cone 1/4" (763637-1) & 3/8" (763619-3), dust nozzle (195559-1), straight guide (122965-7), templete guide 10 (343577-5), wrench 13 (781039-9) & 22 (781011-1).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

M4-052023-1

# Makita Cordless Trimmer DRT50 6 mm (1/4"), 8 mm (3/8")

## Cordless for easy maneuverability and 4 different bases for added versatility

**4**  
different bases



## CÔNG TY TNHH MAKITA VIỆT NAM

Kho 5/5, Block 16, 18L1-2 Đường số 3, KCN VSIP, P. Hòa Phú, TP. Thủ Đức, Bình Dương  
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

**CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC**  
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSIP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.  
ĐT: 0222 376 5942 Fax: 0222 376 5941

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI**  
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.  
ĐT: 0243 202 2585

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG**  
1102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.  
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ**  
366 Võ Văn Kiệt, Khu Vực 3, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ.  
ĐT: 0292 389 4358 Fax: 0292 389 4359

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUƠN MA THUỘT**  
88 Lê Đức Thọ, P. Thống Nhất, TP. Buôn Ma Thuột, T. Đắk Lắk.  
ĐT: 0262 355 4556 Fax: 0262 355 4557

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG**  
Số 01 Lê Đức Thọ, Di An Hoàng Hai Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.  
ĐT: 0225 863 1529

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG**  
Lô 56-58 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa.  
ĐT: 0258 220 0039

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH**  
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.  
ĐT: 0283 821 5191



## Cordless for easy maneuverability

**18V**  
LITHIUM-ION  
Powered by LXT 18V Li-ion batteries

BL motor delivers the power and performance for corded demands

**BL**  
MOTOR

High durability and accuracy obtained by using aluminum for body housing

Accepts 6mm & 8mm collets, 1/4" & 3/8" collets.



Push button switch

Lock/unlock button

On/off switch button

Variable speed control by dial

Shaft lock, Flat-top design and Horizontally installed power supply cord provides stability for easier bit change.

Dual LED job lights illuminate cutting edge and increase visibility



## Available in various combinations for added versatility



### with Trimmer base

Round base for smooth and fast cutting with easy handling



Enlarged opening section of base assembly for excellent bit visibility while maintaining durability.

Non-slip elastomer-covered body grip for increased operator comfort.

Precision cutting depth adjustment

Simple and efficient base lock system

High durability and accuracy obtained by using aluminum for trimmer base

Replaceable, non-marring plastic base plate for protection of trimmer base and smooth sliding on work surface



### with Plunge base (option)

Precision cutting depth adjustment  
Plunge capacity: 0 - 35mm (0 - 1-3/8")



Ergonomically contoured knob style handles



Optional Fine adjusting straight guide can be used.

Easy-to-operate lock lever

Rubberized soft grip

3 stage cut depth adjustment


High durability and accuracy obtained by using aluminum for plunge base

Replaceable, non-marring plastic base plate for protection of plunge base and smooth sliding on work surface



### with Tilt base (option)

Ergonomic body grip easy-to-grasp with one hand  
Tilting capacity: -30° to 45°



Enlarged opening section of base assembly for excellent bit visibility.

Non-slip elastomer-covered body grip for increased operator comfort.

Precision cutting depth adjustment

Simple and efficient base lock system

High durability and accuracy obtained by using aluminum for base holder

Replaceable, non-marring plastic base plate for protection of plunge base and smooth sliding on work surface



### with Offset base (option)

Able to trim close to wall and tight corners with a bit set in offset position.



Able to cut close to a wall or corner-18.5mm at closest



Non-slip elastomer-covered body grip for increased operator comfort.

Simple and efficient base lock system

High durability and accuracy obtained by using aluminum for offset base

Replaceable, non-marring plastic base plate for protection of trimmer base and smooth sliding on work surface

