

Model: DSC191 | Category: Cutting (Metal) | Last Modified: Nov 20 2018 09:53:46



DSC191

Cordless Steel Rod Cutter

18V LXT Li-Ion Cordless 20 mm (3/4") Steel Rod Cutter

Li-Ion

6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

18V**LXT**

Standard Equipments:

Wrench, Hex Wrench, Oil supply (country-specific)

Download:

[Still Photo](#)[Action Photo](#)[Detail & Spec](#)[Related Contents](#)[Related Local Models](#)[Related Accessories](#)[☰ Related Phrase](#)[↓ Technical Info.](#)[↓ Parts List](#)

Detail

- 18V LXT Li-Ion Cordless 20 mm (3/4") Steel Rod Cutter
- Quick and effortless rebar cutting for maximum jobsite productivity and safety
- Ideal for cutting steel bars laid in concrete slab
- Up to 150 cuts of 20 mm rebar with a 6.0Ah LXT battery
- Cutting capacity range of 3 - 20 mm standard rebar
- 4-Way rotatable cutting blade provides up to 4,000 cuts before needing to be replaced
- Cutting head rotates 360° for different cutting positions
- 360° Rotating side handle allows operator to hold tool at most comfortable position
- Adjustable stopper holds the rebar at 90° to the cutting blade and assists in smooth cutting
- Ergonomic pistol grip handle with soft grip provides increased comfort on the job
- Fast and effortless cutting speed of 6.5 seconds for all rebar sizes
- Spark free cutting of rebar and steel rod ideal for use in sensitive areas

Note

Dolmar model:

MA model: XCS01

- Up to 150 cuts of 13 mm rebar with a 3.0Ah LXT battery
- Up to 105 cuts of 16 mm rebar with a 3.0Ah LXT battery
- Up to 75 cuts of 20 mm rebar with a 3.0Ah LXT battery

Carbon Brush	440	
Cutting Capacity	Dia.: 3 - 20 mm (1/8 - 3/4")	
Cutting Speed (sec)	6.5	
Vibration Level	Cutting Rebar: 2.5 m/s ² or less	
Vibration K Factor	Cutting Rebar: 1.5 m/s ²	
Sound Pressure Level	80.5 dB(A)	
Sound Power Level	90.1 dB(A)	
Noise K Factor	3 dB(A)	
Dimensions (L x W x H)	412 x 212 x 284 mm (16-1/5 x 8-3/8 x 11-1/8")	
Net weight	11.1 - 11.2 kg (24.5 - 24.6 lbs.)	

