



DTD134

Cordless Impact Driver

14.4V LXT Li-Ion Cordless 155 N·m (1,370 in.lbs.) Impact Driver

Li-Ion 6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 1.5 Ah

14.4V

XPT LXT



Standard Equipments:

Belt Clip, Battery, Charger

Detail

- 14.4V LXT Li-Ion Cordless 155 N·m (1,370 in.lbs.) Impact Driver
- Variable speed (0-2,400 RPM & 0-3,200 IPM) provides 155 N·m (1,370 in.lbs.) of Max Torque for a wide range of fastening applications
- Compact design at only 138 mm (5-7/16") long
- Convenient one-touch 6.35 mm (1/4") hex chuck for quick bit changes (country-specific)
- Rubberized soft grip provides increased comfort on the job
- Lightweight for reduced operator fatigue
- Built-in LED light with pre-glow and afterglow illuminates the work area

- Makita's proprietary hammer and anvil impact mechanism are manufactured using the best raw materials with the highest quality steel and unique heat hardening process for maximum fastening and driving power
- Extreme Protection Technology (XPT) is engineered for increased dust and water resistance for operation in harsh job site conditions
- 3-Stage battery gauge indicates battery charge level. (country-specific)
- Reversing switch is conveniently located
- Cosmetic design includes a black hammer case
- Phosphorescent bumper glows in dark places
- Electric brake for maximum productivity and increased operator safety
- Durable, reversible belt clip convenient for temporary tool hanging

Note

MA model: XDT03

MA model: XDT03

Optional accessories

Phillips bits

Socket bits

Drill chucks

Bit piece

Drill bits with 6.35mm Hex shank

Hole saws for Impact driver

Stopper for Impact driver

Hook set (Belt clip)

Tool hanger

Battery protectors

Li-ion Battery BL1430

Li-ion Battery BL1430A

Li-ion Battery BL1415

Fast charger DC18RC

Two port multi fast charger DC18RD

Charger DC18SD/DC24SC

Four port multi charger DC18SF

Automotive charger DC18SE

Spec

Carbon Brush	440
---------------------	-----

Capacity	Machine Screw: M4 - M8 (5/32 - 5/16")	Standard Bolt: M5 - M14 (3/16 - 9/16")
	High Strength Bolt: M5 - M12 (3/16 - 1/2")	Coarse thread (in length): 22 - 125 mm (7/8 - 4-7/8")
	Steel: 22 mm (7/8")	Wood (Auger Bit): 24 mm (15/16")
Hex Shank	6.35 mm (1/4")	
Impacts Per Minute (IPM)	0 - 3,200	0 - 3,200
Max Fastening Torque	155 N·m (1,370 in.lbs.)	Soft: 155 N·m
	Soft: 1,370 in.lbs.	
Vibration Level	12 m/s ²	
Vibration K Factor	1.5 m/s ²	
Sound Pressure Level	92 dB(A)	
Sound Power Level	103 dB(A)	
Noise K Factor	3 dB(A)	
Dimensions (L x W x H)	138 x 79 x 238 mm (5-7/16 x 3-1/8 x 9-3/8")	
Hole Saw Diameter	38 mm (1-1/2")	
Shank/Drive	Hex Shank 6.35 mm (1/4")	
Net weight	1.2 - 1.4 kg (2.6 - 3.1 lbs.)	