



DTD149RAE

Cordless Impact Driver

18V LXT Li-Ion Cordless 165 N·m (1,460 in.lbs.) Impact Driver

Li-Ion 6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

18V **BL1820B(2.0Ah) x 2**

LXT XPT



Standard Equipments:

HOOK 346449-3(1)

TWIST TORSIONBIT PH2-120 1PC B-66743(1)

BATTERY BL1820B SET 197254-9(2)

PLASTIC CARRYING CASE 824979-9(1)

DC18RC FAST CHARGER DC18RC(1)

Detail

- 18V LXT Li-Ion Cordless 165 N·m (1,460 in.lbs.) Impact Driver
- Developed for main applications such as tightening of self-drilling screws or light duty machine screws
- 2,500 max RPM and 165 N·m (1,460 in.lbs.) of max torque
- Compact and lightweight design
- Aluminum hammer case creates the impression of rigidity of the machine
- Dual LED lights with preglow and afterglow functions illuminate the work area more widely

- Extreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Convenient one-touch 6.35 mm (1/4") hex chuck for quick bit changes (country-specific)
- Variable speed (0-2,500 RPM & 0-3,200 IPM) for a wide range of fastening applications
- Soft grip provides increased comfort on the job
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Reversing switch is conveniently located
- Phosphorescent bumper glows in dark places
- Electric brake for maximum productivity and increased operator safety
- Durable, reversible belt clip convenient for temporary tool hanging

Note

Optional accessories

Socket bits

Drill chucks

Belt clip

Drill bits with 6.35mm Hex shank

Hole saws for impact driver

Bit piece

Stopper for impact driver

Tool catcher set

Battery protectors

Li-ion Batteries:

BL1860B

BL1850(B)

BL1840(B)

BL1830(B)

BL1820(B)

BL1815N

Fast charger DC18RC

Two port multi fast charger DC18RD

Charger DC18SD/DC24SC

Four port multi charger DC18SF

Automotive charger DC18SE

Spec

Carbon Brush	448
---------------------	-----

Capacity	Machine Screw: M4 - M8 (5/32 - 5/16")	Standard Bolt: M5 - M14 (3/16 - 9/16")
	High Strength Bolt: M5 - M12 (3/16 - 1/2")	Coarse thread (in length): 22 - 125 mm (7/8 - 4-7/8")
	Steel: 22 mm (7/8")	Wood (Auger Bit): 24 mm (15/16")
Hex Shank	6.35 mm (1/4")	
Impacts Per Minute (IPM)	0 - 3,200	0 - 3,200
Max Fastening Torque	165 N·m (1,460 in.lbs.)	Soft: 165 N·m
	Soft: 1,460 in.lbs.	
Vibration Level	N/A m/s ²	
Vibration K Factor	N/A m/s ²	
Sound Pressure Level	N/A dB(A)	
Sound Power Level	N/A dB(A)	
Noise K Factor	N/A dB(A)	
Dimensions (L x W x H)	135 x 79 x 238 mm (5-5/16 x 3-1/8 x 9-3/8")	
Hole Saw Diameter	38 mm (1-1/2")	
Shank/Drive	Hex Shank 6.35 mm (1/4")	
Net weight	1.3 - 1.6 kg (2.8 - 3.5 lbs.)	