



Cordless Impact Driver
DTD153



High Performance with Brushless DC Motor.

Max tightening torque

170N·m

Lightweight at

1.3kg
(BL1815N)



Aluminum hammer case
creates impression of rigidity.

One-touch bit installation
(For some countries only)
No need to pull bit sleeve for bit installation

Twin LED Job light with pre-glow and afterglow functions




High rotational speed
3,400 rpm

Option

Tool catcher set

enables to hook the machine quickly on a snap hook of waist belt.



Part No. 197043-2

Battery Protector

designed to protect the battery cartridge from dust and dripping water in outdoor applications or harsh environments.



Part No. 195798-3



BL MOTOR

Variable speed control by trigger

Ergonomically designed handle with soft grip
provides comfortable grip and more control while minimizing hand fatigue and pain.

Powered by 18V Li-ion batteries

Belt clip

XPT
EXTREME PROTECTION TECHNOLOGY

Battery / Charger

with Battery fuel gauge



*without Battery fuel gauge



BL1860B (6.0Ah)
BL1850B (5.0Ah)
BL1840B (4.0Ah)
BL1830B (3.0Ah)
BL1820B (2.0Ah)
*BL1815N (1.5Ah)

Fast charger
DC18RC



Charger
DC18SD




Cordless Impact Driver

DTD153RTE / DTD153RFE / DTD153Z


Variable Speed




Brake



Reversing



Built-in Job Light



Carrying Case

Standard Equipment:
(+) Truss head screw M4X12 (266622-8),
hook (346317-0), twist Torsion bit
PH2-120 (B-66743).

Capacity

Machine screw: M4 - M8 (5/32" - 5/16")
Standard bolt: M5 - M16 (3/16" - 5/8")
High strength bolt: M5 - M14 (3/16" - 9/16")
Coarse thread (in length): 22 - 125mm (7/8" - 4-7/8")

Impacts per minute (ipm)

0 - 3,600

No load speed (rpm)

0 - 3,400

Max. fastening torque

170 N·m (1,500 in-lbs)

Vibration Level

13.0 m/s²

Sound Pressure Level

96 dB(A)

Sound Power Level

107 dB(A)

Dimensions (L x W x H)

126x79x238mm (5"x3-1/8"x9-3/8")

Net weight

BL1850B: 1.5kg (3.3lbs)

BL1815N: 1.3kg (2.8lbs)

DTD153RTE: 2 battery 5.0Ah (BL1850B), fast charger (DC18RC)

DTD153RFE: 2 battery 3.0Ah (BL1830B), fast charger (DC18RC)

DTD153Z: Battery & charger are sold separately

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 18/12 Đường số 3, KCN VSP, P. Hòa Phú, TP. Thủ Dầu Một, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho 5, Số 1, Đường Số 6, KCN - BT - DV VSP, Bắc Ninh, P. Phú Chấn,
TP. Từ Sơn, T. Bắc Ninh,
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI

65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2385

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG
102 Trần Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng,
ĐT: 0236 352 5078 / 0236 352 5179 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ

386 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy,
TP. Cần Thơ,
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUỒN MA THUỐC
89 Lê Đức Thọ, P. Thống Nhất, TP. Buon Ma Thuột, T. Đắk Lắk,
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG

Số 01 Lô D4-01, Dự án Hoàng Huy Riverside, P. Thượng Lý,
Q. Hồng Bàng, TP. Hải Phòng,
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHA TRANG
Là 36/36 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc,
TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,
ĐT: 0283 821 5191