



## DTD156

### Cordless Impact Driver

18V LXT Li-Ion Cordless 155 N·m (1,370 in.lbs.) Impact Driver

Li-Ion

6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

18V

**LXT**



#### Standard Equipments:

Belt Clip, Battery, Charger

## Detail

---

- 18V LXT Li-Ion Cordless 155 N·m (1,370 in.lbs.) Impact Driver
- Aluminum hammer case for creating the impression of rigidity
- Compact design with a short overall length of 143mm (5-5/8")
- Variable speed (0-2,500 RPM & 0-3,000 IPM) provides 155 N·m (1,370 in.lbs.) of Max Torque for a wide range of fastening applications
- Compact, lightweight but powerful 4-pole motor
- Rubberized soft grip provides increased comfort on the job
- Lightweight for reduced operator fatigue

- Built-in LED light with pre-glow and afterglow illuminates the work area
- Reversing switch is conveniently located
- Electric brake for maximum productivity and increased operator safety
- Durable, reversible belt clip convenient for temporary tool hanging
- Battery protection circuit protects against overloading, over-discharging and over-heating

## Note

---

MA model: XDT17

Optional accessories

Phillips bits

Socket bits

Drill chucks

Hook

Stopper for Impact driver

Bit piece

Battery protectors

Tool hanger

Battery BL1815N

Battery BL1820(B)

Battery BL1830(B)

Battery BL1840(B)

Battery BL1850(B)

Battery BL1860B

Fast charger DC18RC/ DC18RE

Charger DC18SD/ DC24SC

Two port multi fast charger DC18RD

Two port multi charger DC18SH

Automotive charger DC18SE

Four port multi charger DC18SF

## Spec

---

<b>Carbon Brush</b>	5	
<b>Capacity</b>	<b>Machine Screw:</b> M4 - M8 (5/32 - 5/16")	<b>Standard Bolt:</b> M5 - M14 (3/16 - 9/16")
	<b>High Strength Bolt:</b> M5 - M12 (3/16 - 1/2")	<b>Coarse thread (in length):</b> 22 - 125 mm (7/8 - 4-7/8")
	<b>Steel:</b> 22 mm (7/8")	<b>Wood (Auger Bit):</b> 24 mm (15/16")

<b>Hex Shank</b>	6.35 mm (1/4")	
<b>Impacts Per Minute (IPM)</b>	0 - 3,000	0 - 3,000
<b>Max Fastening Torque</b>	155 N·m (1,370 in.lbs.)	<b>Soft:</b> 155 N·m
	<b>Soft:</b> 1,370 in.lbs.	
<b>Max Output</b>	230 W	
<b>Vibration Level</b>	10.0 m/s <sup>2</sup>	
<b>Vibration K Factor</b>	1.5 m/s <sup>2</sup>	
<b>Sound Pressure Level</b>	92 dB(A)	
<b>Sound Power Level</b>	103 dB(A)	
<b>Noise K Factor</b>	3 dB(A)	
<b>Dimensions (L x W x H)</b>	<b>w/ BL1815N / BL1820B:</b> 143 x 79 x 23 mm (5-5/8 x 3-1/8 x 8-3/4")	<b>w/ BL1830B / BL1840B / BL1850B / BL1860B:</b> 143 x 79 x 241 mm (5-5/8 x 3-1/8 x 9-1/2")
<b>Hole Saw Diameter</b>	38 mm (1-1/2")	
<b>Shank/Drive</b>	Hex Shank 6.35 mm (1/4")	
<b>Net weight</b>	1.3 - 1.6 kg (2.9 - 3.6 lbs.)	