

Wide range of accessories available for various applications

Please see "Accessories for Multi Tool" for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)



Applications:
Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve different angles to allow easy operation in tight spaces.

Cutting



Applications:
Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Able to perform long distance push cut.
- The segment shape allows flush cutting.

Sanding



Applications:
Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers.

Benefits:

- Able to sand in corners.
- Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles



Applications:
Replacing broken wall or floor tile.

Benefits:

- Less amount of dust scattering thanks to oscillating action.
- The segment shape allows flush cutting.

Scraping



Applications:
Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:
Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.

Dust extraction system (Option)

Part No. 196765-1



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.

Cordless Multi Tool		DTM51RFE10 / DTM51Z	
	Variable Speed	DTM51	
	Soft Start	Oscillations per minute (opm)	6,000-20,000
	Dust Collecting	Dimensions (L x W x H)	326x80x122mm (12-7/8"x3-1/8"x4-13/16") with BL1815 340x80x122mm (13-3/8"x3-1/8"x4-13/16") with BL1830
	Carrying Case	Net weight*	2.0kg (4.4lbs) with BL1815 or BL1815N 2.2kg (4.9lbs) with BL1830 or BL1840
Standard Equipment : Plastic carrying case (821608-5), cut saw 28 (B-21353), cut saw 32 (B-64814), abrasive paper deltared long 60(B-21565), 120 (B-21593), 240 (B-22931), sanding pad (B-21537)(B-46202)			
<small>*weight according to EPTA-Procedure 01/2003</small>			

CÔNG TY TNHH MAKITA VIỆT NAM

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG
102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ
366 Võ Văn Kiệt, Khu Vực 5, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG
Số 01 Lê Đại Hành, Di An Hoàng Hai Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191



Cordless Multi tool DTM51

Satisfy Professional's Needs



Tool-less Accessory Change

Lever style lock system allows for quick installation and replacement of the accessories.



Compatible with all OIS accessories (Oscillating Interface System)



Photo : DTM51

Extra Versatility

Wide selection of accessories available for various applications



The standard equipment may vary by country.

M4-052023-1



Cutting PVC, FRP pipes



Cutting metals



Wood flush cutting



Wood plunge cutting



Deep plunge cutting



Sanding and polishing various materials



Cutting tiles



Removing mortar, tile adhesive



Routing joints on wall tiles



Corner cutting



Cutting window putty, silicone



Cutting polystyrene, rubber



Scraping floor tiles

High operation efficiency

- Up to 20,000 oscillations per minute
- 3.2° oscillation angle



Variable speed control by dial

Anti-restart function

Battery capacity warning lamp

Soft start

allows accurate landing of the blade on the surface of workpiece in various applications.

Photo: DTM51

Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.

Items of standard equipment may vary by country or area.

Ergonomically best possible barrel grip



- ergonomically designed to suit many different ways to grip required in many different applications with a wide range of accessories.
- with the on-off slide switch so ergonomically positioned that you can turn it on/off with the finger of your hand holding the grip.

Powered by Li-ion Battery

DTM51

BL1850
5.0 Ah



BL1840
4.0 Ah



BL1830
3.0Ah



BL1815/N
1.3/1.5Ah



DTM41

BL1440
4.0 Ah



BL1430
3.0Ah



BL1415
1.3Ah

