



Cordless Impact Wrench DTW180 3/8" (9.5 mm)



More Compact and Lightweight

Reverse rotation
auto stop mode

Max Fastening Torque

180N·m



Slim motor housing thanks to compact BL motor

144mm

55mm

BL MOTOR

Lightweight and Compact new BL motor

Twin LED job light with preglow and afterglow functions

Variable speed control by trigger

Electronic 2 stage impact power selection

Impact power selection: Soft / Hard

Reverse rotation auto stop mode
When the bolt/nut gets loosened enough, the tool stops in 0.2 seconds.

Best possible ergonomic handle for screwing applications

A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically designed and widened to perfectly fit the U-shape formed between user's thumb and index finger.

B Ribbed soft grip enables all finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation.

XPT
EXTREME PROTECTION TECHNOLOGY

Accessories

Tool catcher set

part No.
197043-2



Tool catcher set (with shoulder belt)

part No.
197941-0
197942-8 (EU)



Li-ion Battery & Charging Time Reference, Compatibility Chart

18V LITHIUM-ION	DC18RC	DC18RD	DC18SD
BL1815N 1.5Ah	15 min	30 min	
BL1820B 2.0Ah	24 min	45 min	
BL1830B 3.0Ah	22 min	60 min	
BL1840B 4.0Ah	36 min	90 min	
BL1850B 5.0Ah	45 min	110 min	
BL1860B 6.0Ah	55 min	130 min	

Cordless Impact Wrench

DTW180RFE/DTW180Z 3/8" (9.5 mm)

Variable Speed	Fastening Capacities	Standard Bolt: M8 - M16 (5/16" - 5/8") High Tensile Bolt: M6 - M12 (1/4" - 1/2") 9.5 mm (3/8")
Brake	Square Drive	9.5 mm (3/8")
Reversing	No Load Speed (RPM)	Hard / Soft: 0 - 2,400 / 0 - 1,300
Electronic 2-Speed	Impacts Per Minute (IPM)	Hard / Soft: 0 - 3,600 / 0 - 2,000
Built-in Job Light	Max Fastening Torque	180 N·m (130 ft.lbs.)
Carrying Case	Vibration Level	Impact tightening of fasteners of the maximum capacity of the tool: 9.0m/s ²
	Sound Pressure Level	89 dB(A)
	Sound Power Level	100 dB(A)
	Dimensions (L x W x H)	w/ BL1815N / BL1820B: 144x79x218 mm w/ BL1830B / BL1840B / BL1850B / BL1860B: 144x79x235 mm
	Net weight	1.2 - 1.5 kg (2.7 - 3.4 lbs.)
	DTW180RFE:	2 battery 3.0Ah (BL1830B), fast charger (DC18RC)
	DTW180Z:	Battery & charger are sold separately

Standard equipment:

Hook (346317-0), (+) truss head screw M4X12 (266622-8) (socket not include).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 181-12 Đường số 3, KCN VSP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.
ĐT: 0243 202 2385

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG
102 Triều Nữ Hoàng, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.
ĐT: 0236 352 5078 / 0236 352 5179 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ
386 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy, TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUỒN MA THUỐC
88 Lê Đức Thọ, P. Thống Nhất, TP. Buon Ma Thuột, T. Đắk Lắk.
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG
Số 01 Lô D1-01, Dự án Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG
Là 3636 đường B6, Khu đô thị Vinh Diêm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191

A4-052023-1