



Cordless Pole Saw DUA300 / DUA301 300mm (12")



* These models are not compatible with Portable Power Pack (PDC1200, PDC01) / Only rear handle type chainsaws are compatible

Accessories

Standard equipment

Guide bar / Saw chain / Guide bar cover

Cutter type: MC : Micro chisel, CC: Chamfer chisel

Guide Bar				Saw Chain						Bar Cover	Drive sprocket			
Bar length	Motor Mount	Type	Part no.	No.of drive links	Gauge	Pitch	Type OREGON / DOLMAR	Cutter type	Part no.	Part no.	Type	Part no.		
25cm	A041	Lam bánh xe	191G14-3/161846-0 Limited quantity	40	1.1mm/ .043"	3/8"LP	90PX	CC	191H00-0/199075-5 Limited quantity	458501-6	Sprocket 3/8"LP	226992-7		
30cm			191G15-1/165245-8 Limited quantity	46					191H01-8/196740-7 Limited quantity	419288-5				
25cm			191G22-4/168408-5 Limited quantity	40	1.3mm/ .050"		91PX		191H08-4/196205-9 Limited quantity	458501-6				
30cm			191G23-2/165200-0 Limited quantity	46					191H10-7/531492646/196211-4 Limited quantity				419288-5	

Band assembly set

Part No.
191K37-5



Portable Power Pack

PDC1200A02

Powered by
36V-40Vmax
built-in
battery



Adapter set (18V x2)

Part No. 191J51-5



Charging Time

18V LITHIUM-ION	DC18RD
BL1815N 1.5Ah	15 min
BL1820B 2.0Ah	24 min
BL1830B 3.0Ah	22 min
BL1840B 4.0Ah	36 min
BL1850B 5.0Ah	45 min
BL1860B 6.0Ah	55 min

Cordless Pole Saw

DUA300ZB / DUA301ZB 300 mm (12")

	Variable Speed	Guide Bar Length	DUA300 300 mm (12") Gauge: 1.3 mm (0.043 / 0.050") Pitch : 3/8"	DUA301 300 mm (12") Gauge: 1.3 mm (0.043 / 0.050") Pitch : 3/8"
	Brake	Saw chain	0 - 20.0 m/s (0 - 1,200 m/min)	0 - 20.0 m/s (0 - 1,200 m/min)
	Soft Start	Chain Speed	(0 - 3,940 FPM)	(0 - 3,940 FPM)
		Oil Tank Capacity	160 mL	160 mL
		Vibration level (Front / Rear)	1.2 m/s ²	Not extended: 2.2 m/s ² Extended: 2.3 m/s ²
		Noise level	103 dB(A)	105 dB(A)
		Dimensions (L x W x H)*	2,238 x 155 x 191 mm	2,530 - 3,762 x 155 x 191 mm
		Net weight	6.1 - 6.8 kg (13.5 - 15.0 lbs.)	7.8 - 8.4 kg (17.2 - 18.5 lbs.)
		*without guide bar		

Standard Equipment :

Guide bar (165200-0), chain cover (419288-5), wrench 13-16 (782023-7), band (191K37-5).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

A4-052023-1

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 456, Block 16, 18L1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 382 8338 - Fax: 0274 382 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSPP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 - Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG
102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079 - Fax: 0236 352 5179

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ
366 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy, TP. Cần Thơ
ĐT: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUƠN MA THUỘT
88 Lê Đức Thọ, P. Thắng Mỹ, TP. Buôn Ma Thuột, T. Đắk Lắk
ĐT: 0262 355 4556 - Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG
Số 01 Lê Duẩn, Dị an Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng
ĐT: 0225 883 1519

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHÀ TRẢNG
Lô 36-38 đường B6, Khu đô thị Vĩnh Diễm Trung, Xã Vĩnh Ngọc, TP. Nhà Trảng, T. Khánh Hòa
ĐT: 0258 220 0639

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
ĐT: 0283 821 5191



Efficient cutting with ease

No load chain speed
20.0 m/s

300mm (12")

DUA300 Fixed length

DUA301 Telescopic

Total length
2,238mm*
Fixed length

Telescopic
Total length
2,530 - 3,762mm*

*without guide bar


18V + 18V → 36V

BL MOTOR XPT



18v + 18v → 36v

Delivers equivalent performance of 30 mL class engine models



Saw head weight
0.7kg

Telescopic pole
(DUA251 / DUA301 only)
Tool-less pole extension and fixing for easy adjustment of pole length

Excellent tool balance

The motor is located in the battery housing at the bottom of the tool. This bottom-mounted motor reduces the saw head weight, allowing for:

- Ease to control the saw head for easy access to a desired cutting position
- Reduced user fatigue and stress



High operating efficiency

High power BL motor delivers the same or higher operation efficiency than 30mL class engine models.

Normal mode

Cut 100x100 Cedar square timber /
Pressing load:
blade-tip pressing load 30N / 90PX

Work efficiency

1.6sec

Work amount
(on a single full battery charge)

238 pcs.

Cordless Pole Saws

300mm (12")

DUA300 **Fixed length**

DUA301 **Telescopic**

300mm (12")



Retractable oil tank cap knob
decreases the chance that the saw head will be snagged in branches.

Slim saw head

The same slim design as engine pole saws provides easy maneuverability into branches.

Saw head width
87mm

Chain oil tank with high transparency
allows to easily check the amount of remaining oil.



Anti-fall captive nut



Integrated branch hook
convenient for removing cut branches from trees

Torque boost mode

raises the current limit temporarily for easy cutting of trunks or thick limbs.

ø200 cedar timber / Pressing load:
blade-tip pressing load 30N / 90PX

Work efficiency

6.2sec

Maximum total length
3,762 mm
Shortest total length
2,530 mm

Telescopic

Total length
2,238 mm

Fixed length

Battery guard
also can be used as an auxiliary grip.