Hole on the bottom of housing for hanging the machine

Dual battery fuel gauge

indicates the power remaining in each battery individually in 3 LED stages.

Shoulder belt













*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BF-AF



The most powerful Cordless blower

(Blower function only)

Excellent handling and comfortable operation by excellent balance







6-stage air volume/velocity selection just by adjusting dial.





Best grip angle and an nozzle angle for efficient sweeping operation.



Powered by two battery system in series

•Two 18V Li-ion batteries can be directly installed on the machine to supply more energy to the powerful 36V DC motor drive system.





(min)

3-stage telescopic long nozzle with an adjustment range of 100mm (4")



Lightweight
3.5kg (7.7lbs)
[with 2.0Ah battery]

Continuous run time (approx) on a single full charged battery

			Paskith Eller/S	mastic constitution	makita EEE / SV
dial	BL1815N x2	BL1820 x2	BL1830 x2	BL1840 x2	BL1850 x2
1	24	33	44	61	75
2	13	18	25	34	42
3	9	12	16	23	28
4	6	9	12	17	20
5	5	7	9	13	16
6	4	5	6.3	9.3	11.4
Charging time	15	24	22	36	45
		Port Multi Charger		DC18RD	
		19/9/4/			

Longer runtime

Longer runtime compared to the competitors. (based on the same air volume and velocity)



Reduced noise level

Makita DUB362 features:

- 3 blade fan to reduce noise level without losing air volume and velocity
- Double housing structure to minimize the noise level
- Additional sponge inside the housing to absorb the noise level

