# Accessories

## Hose

Note: Al though type B hose can be connected with power tools, Front cuffs and Joint are required

for some power tools

A: for power tools

B: for cleaning



Size	Length (m)	Туре	with Front cuffs	Part No.
28mm	1.5	Α	22, 38	A-34235
28mm	2.5	А	22, 24, 38	195437-5
28mm	3.5	Α	22, 24, 38	195433-3
28mm	5	А	22, 24, 38	195436-7
38mm	2.5	В	38	195434-1
38mm	5	В	38	195435-9

## Straight pipe, Bending pipe, Anchor nozzle set and

## Corner nozzle



# **Nozzle assembly**



Туре	Dry/ Wet	Part No.
Universal Type	Dry/ Wet	195551-7
Compact Type A	Dry	195549-4
Compact Type B	Wet	195550-9
Wide Type	-	A-47846

## Holder set 10-33





# **Cleaning set**

Includes one each of:

-Bending pipe

-Nozzle assembly

-Corner nozzle



# **Round brush**



## Front cuffs & Joint



туре	Part No.
Front cuffs 22	195547-8
Front cuffs 24	195546-0
Front cuffs 38	195545-2
Joint 22-38	195548-6

## Filter set









Powder filter set	Prefilter set	Cloth filter	Filter set (for water)
Part No.	Part No.	Part No.	Part No.
*197166-6	195553-3	140248-3	195555-9

## Damper set



195552-5

## Poly bag set



Per pkg.	Part No.
10	195432-5

## Filter bag set



195557-5

# **Corded and Cordless Vacuum Cleaner DVC860L** (Wet & Dry / Cloth filter type) **DVC861L** (Only Dry / HEPA filter)



Double Insulation

Suction power Max peak air flow AC: 320W DC: 25-70W AC: 3.6m3/min DC: 2.1m3/min Max sealed suction AC: 24kPa DC: 9kPa Dust:8L Water: 6L (DVC860L only)  $(L \times W \times H)$ (14-3/8"x13-1/8"x14-1/2") DVC860L (BL1820x2): 8.6kg (19.0lbs) Net weight DVC860L (BL1850Bx2): 9.2ka (20.3lbs) DVC861L (BL1820x2): 9.3kg (20.5lbs) Power supply cord

DVC860L: Connection cord. Tool box. Hose complete, Poly bag set (10 pcs), Straight pipe, Bending pipe, Corner nozzle,

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

# CONG TY TNHH MAKITA VIET NAM KIN 4-5-9, Block 16, 18L1-2 Dulong as G. KCN VSIP II, P. Hoa Pilo, TP. Thú Dàu Một, Binh D 6T: 0274 552 8338 - Fax: 0274 552 8339 - Websitz: www.makita.com.un

CHÍ NHÁNH CTY TNHH MAKÍTA VN TAI MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NÔI

195439-1

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH







Suction power Max air flow

**70** w

Max sealed suction 9.0 kPa



**2.1** m<sup>2</sup>/min




# On DC power + On AC power



Max air flow **3.6** m<sup>2</sup>/min Max sealed suction **24.0** kPa







Removable power supply



# **Continuous run time**


On a single full battery charge: minute				
Battery		BL1850B [5.0Ah]	BL1840B [4.0Ah]	BL1830B [3.0Ah]
Run time	High	30min.	25min.	20min.
	Low	65min.	50min.	40min.
Charging ti	me			
DC18RD	Carried States	45min.	36min.	22min.
DC18RC		45min. × 2	36min. × 2	22min. × 2
DC18SD		110min. × 2	90min. $ imes$ 2	60min. × 2





Large on-off switch

- allows for easy on/off switching. • functions only when Main power
- switch is on to prevent accidental switch-on during transportation, etc.



Dual battery fuel gauge



Variable suction power control by dial



Caster stopper







On-tool pipe storage

