







Work volume on a single full battery charge

about 5,000 nails

with battery: BL4025 nail: Length 15-40 mm, Gauge 18 Ga





40Vmax series movie



40Vmax mechanism movie




This movie was filmed in Japan. Models and specs may vary by country.

High power

40Vmax XGT Li-lon battery and BL motor quickly re-compress the spring for next firing.

Counterweight mechanism

reduces vibration by moving a counterweight in the opposite direction of the hanmmer.



Compact and lightweight design

for high maneuverability

Lightweight at 2.6kg

(with BL4020)

243_{mm}



Tough spring



Contact top designed for easy nail placement

Nail shooting port is located in the center of contact arm. enabling accurate nail placement.



Slim nose with nose adapter



Driving depth adjustment



LED job light





Accessories

Nose Adapter S Part No. 422665-2





Battery Charging Time Reference

40 Viction max	DC40RA [ESSIGNATION]	DC40RC
BL4050F 5.0Ah	50min	85min
BL4040 4.0Ah	45 _{min}	67min
BL4025 *12.5Ah	28 _{min}	38 _{min}
BL4020 *12.0Ah	22 _{min}	30 _{min}

^{*1} Recommended battery

Cordless Brad Nailer FN001G







Standard Equipment:

Safety Goggles, Nose Adapter, Hex Wrench, Belt Clip, Battery, Charger

Capacity

Magazine Capacity Shot q'ty on a single full battery charge Vibration Level Sound Pressure Level Sound Power Level

Dimensions (L x W x H)

Net weight

Length: 15, 20, 25, 30, 35, 40 mm (5/8, 3/4, 1, 1-3/16, 1-3/8, 1-5/8") Gauge: 18 Ga w/BL4025: 5,000

2.5 m/s² or less 81 dB(A) w/o Battery: 234 x 86 x 243 mm (9-1/4 x 3-3/8 x 9-9/16") w/BL4020/BL4025: 265 x 86 x 243 mm (10-3/8 x 3-3/8 x 9-9/16") w/BL4050F: 291 x 86 x 263 mm (11-1/2 x 3-3/8 x 10-3/8") 2.6 - 3.2 kg (5.7 - 7.1 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan