

Thorough prevention measures for scratch-free car polishing

Tool rest with elastomer



Tool can be put upside down without damaging car body by tool rest with elastomer.

Turned up power supply cord



PO6000C
150 mm (6")



PO5000C
125 mm (5")



Detachable, rubber type vent dust cover

to prevent wool fibers from entering into the motor



Selectable maneuverability by applications

Front grip + Main grip

Easy to grip head not only for bonnet work but for sideway work



Side grip + Main grip

Side grip is available (option)



Main grip



Variable speed dial & trigger



Setting up RPM at full up position of trigger is easy by a variable speed dial. Variable speed control by trigger enables to adjust RPM during operation.

Accessories

Pad

(hook & loop type)



| Size | Part No. | Part No. (EU) |
|-------|----------|---------------|
| 100mm | 197926-6 | 197925-8 |
| 125mm | 197923-2 | 197922-4 |
| 150mm | 197929-0 | 197928-2 |

Sponge pad

(hook & loop type)

(For wax coating)



| Size | Part No. | Part No. (EU) |
|-------|----------|---------------|
| 100mm | 197912-7 | 197893-5 |
| 125mm | 794558-6 | - |
| 150mm | 197914-3 | 197894-3 |

Wool pad

(hook & loop type)

(For high gloss polishing)



| Size | Part No. | Part No. (EU) |
|-------|----------|---------------|
| 100mm | 197918-5 | 197896-9 |
| 125mm | 197920-8 | 197897-7 |

Felt pad

(hook & loop type)

(For removing wax)



| Size | Part No. | Part No. (EU) |
|-------|----------|---------------|
| 100mm | 197916-9 | 197895-1 |
| 125mm | 196152-4 | - |

Random Orbit Polisher

PO5000C 125 mm (5") / PO6000C 150 mm (6")

318

| | PO5000C | PO6000C |
|-------------------|---------------------------------|---------------------------------|
| Double Insulation | 900W | 900W |
| Variable Speed | 125 mm (5") | 150 mm (6") |
| Constant Speed | 0 - 6,800 | 0 - 6,800 |
| Soft Start | 0 - 13,600 | 0 - 13,600 |
| Hook & Loop | 0 - 780 | 0 - 780 |
| | 5.5 mm (7/32") | 5.5 mm (7/32") |
| | Polishing: 6.5 m/s ² | Polishing: 7.0 m/s ² |
| | 81 dB(A) | 83 dB(A) |
| | 92 dB(A) | 94 dB(A) |
| | 451x123x134mm | 451x148x126mm |
| | (17-3/4"x4-7/8"x5-1/4") | (17-3/4"x5-7/8"x5") |
| | 2.8 kg (6.2 lbs) | 2.8 kg (6.2 lbs) |
| | 4.0 m (13.1 ft) | 4.0 m (13.1 ft) |

Standard Equipment: Side grip (country-specific), Pad (country-specific), Hex Wrench

weight according to EPTA-Procedure 01/2003
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201706



Random Orbit Polisher

PO5000C 125mm(5")


PO6000C 150mm(6")

Versatile one for various
polishing operations
from scratch removal to fine finishing



Selectable 2 rotation modes

Rough Polishing




Forcible rotation mode

Orbital action with forced rotation of the pad for rough polishing such as scratch removal.



Fine Polishing



Free rotation mode

Orbital action with free rotation of the pad for fine polishing.