

[Back](#)[Scroll To Top](#)

DHR202

Model

[Detail & Spec](#)[Related Contents](#)[Related Local Models](#)[Related Accessories](#)

Model: DHR202 | Category: Impact Drilling / Demolition | Last Modified: Sep 19 2019 11:09:28



## DHR202

### Cordless Combination Hammer

20 mm (13/16") Adapted for SDS-PLUS bits

18V LXT Li-Ion Cordless 20 mm (13/16") Combination Hammer, SDS-PLUS Bits

**Li-Ion**

6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

**18V****LXT**

#### Standard Equipments:

Charger, Battery, Side Grip, Depth Gauge

Download:

[Still Photo](#)[Action Photo](#)[Action Photo2](#)[☰ Related Phrase](#) | [↓ Technical Info.](#) | [↓ Parts List](#)

### Detail

- 18V LXT Li-Ion Cordless 20 mm (13/16") Combination Hammer, SDS-PLUS Bits
- Makita-built motor delivers 0-1,100 RPM and 0-4,000 BPM for 2X faster drilling
- Synchronized RPM and BPM minimizes overlapping impacts for up to 50% more efficient drilling
- 3-mode operation; "rotation only", "hammering with rotation" and "hammering only"
- 40 different chisel positions for increased comfort and performance
- Built-in torque limiter clutch disengages motor should bit bind
- Compact design and lightweight for reduced operator fatigue
- Compact, ergonomic design with large 2-finger trigger

### Note


Dolmar model:


MA model: XRH03

Optional accessories

- \* SDS-Plus bits
- \* Taper shank T.C.T bits
- \* Taper shank adapter
- \* Cotter
- \* Drill chuck assembly
- \* Drill chuck S13
- \* Chuck key S13
- \* Keyless drill chuck



 Back

 Scroll To Top


DHR202

Model

## Detail &amp; Spec

## Related Contents

## Related Local Models

## Related Accessories

electrical contact

- One touch sliding chuck enables quick and easy bit changes
- Ergonomic soft rubber grip design for vibration absorption and comfortable operation
- Depth gauge for increased drilling consistency
- Side grip with elastomer soft grip
- Variable speed trigger allows operator to adjust speed based on materials or application
- Conveniently located push button for rotation reverse
- Electric brake for maximum productivity and increased operator safety
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Externally accessible brushes for easy serviceability

- \* Scaling chisels
- \* Bull points
- \* Dust cup set
- \* Dust cups
- \* Grease Vessel 30g
- \* Bit grease
- \* Blow out bulb
- \* Safety goggle
- \* Dust extractor attachment
- \* Joint 25
- \* Hose
- \* Hammer service kit
- \* Charger DC18RA
- \* Charger DC18SC
- \* Charger DC24SA
- \* Charger DC24SC

<b>Carbon Brush</b>	441	
<b>Capacity</b>	<b>Concrete:</b> 20 mm (13/16")	<b>Concrete / Steel / Wood:</b> 20 / 13 / 26 mm (13/16 / 1/2 / 1")
	<b>Core Bit:</b> 54 mm (2-1/8")	<b>Steel:</b> 13 mm (1/2")
	<b>Wood:</b> 26 mm (1")	<b>Diamond Core Bit:</b> 32 mm (1-1/4")
	<b>Masonry:</b> 20 mm (13/16")	<b>Wood (Auger Bit):</b> 26 mm (1")
	<b>Wood (Self-Feed Bit):</b> 26 mm (1")	
<b>Blows Per Minute (BPM)</b>	0 - 4,000	
<b>Chuck Capacity</b>	1.5 - 13 mm (1/16 - 1/2")	
<b>Vibration Level</b>	<b>Hammer Drilling into Concrete:</b> 14.5 m/s <sup>2</sup>	
<b>Sound Pressure Level</b>	87 dB(A)	

[Back](#)[Scroll To Top](#)

DHR202

Model

Detail & Spec	Related Contents	Related Local Models	Related Accessories
<b>Quick Change Drill Chuck</b>	NO		
<b>Shank Type</b>	<b>Hammer:</b> SDS-PLUS Shank		
<b>Net weight</b>	3.2 - 4 kg (7.1 - 8.8 lbs.)		