



GR Browse

System

About Area

About Security

Back


Search dhr241



Conditional Search

Model

Model: DHR241 | Category: Impact Drilling / Demolition | Last Modified: Nov 28 2018 11:26:34



DHR241

Cordless Combination Hammer

20 mm (13/16") Adapted for SDS-PLUS bits

18V LXT Li-Ion Cordless 20 mm (13/16") Combination Hammer, SDS-PLUS Bits

Li-Ion

6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

18V



Standard Equipments:

Charger, Battery, Side Grip, Depth Gauge

Download:

[Still Photo](#)
[Action Photo](#)
[Detail & Spec](#)
[Related Contents](#)
[Related Local Models](#)
[Related Accessories](#)


Related Phrase

Technical Info.

Parts List

Detail

- 18V LXT Li-Ion Cordless 20 mm (13/16") Combination Hammer, SDS-PLUS Bits
- 0 - 1,100 RPM and 0 - 4,000 BPM for Demanding Applications
- Makita-built variable speed motor delivers 0-1,100 RPM and 0-4,000 BPM
- Synchronized RPM and BPM minimizes overlapping impacts for up to 50% more efficient drilling
- 3-mode operation: "rotation only", "hammering with rotation" or "hammering only"
- Job site tested shock absorbent handle protects the battery housing for durability
- Built-in clutch reduces gear damage by disengaging gears if bit binds
- One-touch sliding chuck for quick bit changes

Note

Dolmar model:

MA model: XRH04

Optional accessories

- * SDS-Plus bits
- * Taper shank T.C.T bits
- * Taper shank adapter
- * Cotter
- * Drill chuck assembly
- * Chuck adapter
- * Drill chuck S13
- * Chuck key S13
- * Keyless drill chuck



GR Browse

System

About Area

About Security

Back

Search dhr241



Conditional Search

Model

- Rubber joint construction suppresses transmission of vibration to battery, minimizing battery failures due to terminal breakage or poor electrical contact
- Rubber housing bumper protects mode selector switch and gear housing from damage
- Ergonomic soft rubber grip design for vibration absorption and comfortable operation
- Side grip with elastomer soft grip
- 1.9 Joules (EPTA) impact energy delivers high performance
- Depth gauge for increased drilling consistency
- Variable speed trigger allows operator to adjust speed based on materials or application
- Conveniently located push button for rotation reverse. □ Electric brake for maximum productivity and increased operator safety. □ Battery protection circuit protects against overloading, over-discharging and over-heating. □ Externally accessible brushes for easy serviceability

- * Scaling crisers
- * Bull points
- * Dust Cup
- * Grease Vessel 30g
- * Blow out bulb
- * Safety goggle
- * Dust extractor attachment
- * Joint 25
- * Charger DC18RA
- * Charger DC18SC
- * Charger DC24SA
- * Charger DC24SC
- * Battery BL1830
- * Hammer service kit

Carbon Brush	441	
Impact Energy	1.9 J	
Capacity	Concrete: 20 mm (13/16")	Concrete / Steel / Wood: 20 / 13 / 26 mm (13/16 / 1/2 / 1")
	Core Bit: 54 mm (2-1/8")	Steel: 13 mm (1/2")
	Wood: 26 mm (1")	Diamond Core Bit: 32 mm (1-1/4")
	Masonry: 20 mm (13/16")	Wood (Auger Bit): 26 mm (1")
	Wood (Self-Feed Bit): 26 mm (1")	
Blows Per Minute (BPM)	0 - 4,000	
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")	
Vibration Level	Hammer Drilling into Concrete: 12.5 m/s ²	Chiselling: 9.5 m/s ²
	Drilling: 2.5 m/s ²	



[GR Browse](#)[System](#)[About Area](#)[About Security](#)[Back](#)

Search

dhr241



Conditional Search

Model

Dimensions (L x W x H)	417 x 84 x 219 mm (16-3/8 x 3-5/16 x 8-5/8")	
Quick Change Drill Chuck	NO	
Shank Type	Hammer: SDS-PLUS Shank	
Net weight	3.2 - 4 kg (7.1 - 8.8 lbs.)	

