

[Back](#)
[Scroll To Top](#)


DHR263

Model

[Detail & Spec](#)
[Related Contents](#)
[Related Local Models](#)
[Related Accessories](#)

Model: DHR263 | Category: Impact Drilling / Demolition | Last Modified: Aug 05 2021 15:20:09



## DHR263

### Cordless Combination Hammer

26 mm (1") Adapted for SDS-PLUS bits

18V X2 (36V) LXT Li-Ion Cordless 26 mm (1") Combination Hammer, SDS-PLUS Bits

**Li-Ion**

6.0 Ah / 5.0 Ah / 4.0 Ah / 3.0 Ah / 2.0 Ah / 1.5 Ah

**18V X2**
**LXT** **36V** **XPT**


#### Standard Equipments:

Side Handle, Depth Gauge, Battery, Charger, Dust Cup (country-specific), Cleaning cloth (country-specific), Bit Grease (country-specific)

Download:

[Still Photo](#)
[Action Photo](#)
[☰ Related Phrase](#)
[↓ Technical Info.](#)
[↓ Parts List](#)

### Detail


- 18V X2 (36V) LXT Li-Ion Cordless 26 mm (1") Combination Hammer, SDS-PLUS Bits
- 18V solution for corded power demands
- Two 18V LXT Li-Ion batteries deliver the power and run time for corded demands without leaving the 18V LXT platform
- Makita-built motor delivers 0-1,250 RPM, 0-5,000 BPM and 3.0 Joules (Makita value) of impact energy for faster drilling
- Vibration absorbing handle provides a sure and comfortable operation
- Ergonomic soft grip handle and large 2-finger trigger provide increased comfort on the job
- LED battery indicators show charge level for each battery
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"
- SDS-PLUS shank rotates 360° with 40 different positions


### Note

MA model: XRH05

Optional accessories

- SDS-PLUS bits
- Taper shank TCT bits
- Taper shank adapter
- Cotter
- Chemical anchor adapter
- Diamond core bits
- Grip drills
- Grip drill holder
- Drill chuck assembly
- Grooving chisels

 Back

 Scroll To Top


DHR263

Model

## Detail &amp; Spec

## Related Contents

## Related Local Models

## Related Accessories

- LED light illuminates drilling surface for more productivity in low light applications
- Extreme Protection Technology (XPT) engineered to provide increased dust and water resistance in harsh job site conditions
- Reverse switch operable by one hand
- Optional dust cup for a cleaner work environment
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Externally accessible brushes for easy serviceability
- Depth gauge for increased drilling consistency (country-specific)

Scraper assembly

Dust cup

Dust cup 5

Dust cup 9

Dust extractor attachment

Grease vessel 30g

Bit grease

Blow out bulb

Hammer Service Kit

Battery BL1815N

Battery BL1830

Battery BL1840

Fast charger DC18RC

Charger DC18SD


Charger DC24SC


Quad Port Charger DC18SF

Automotive charger DC18SE



<b>Carbon Brush</b>	442	
<b>Impact Energy</b>	<b>EPTA-Procedure 05/2009:</b> 2.5 J	<b>Our experimental conditions:</b> 3 J
<b>Capacity</b>	<b>Concrete:</b> 26 mm (1")	<b>Concrete / Steel / Wood:</b> 26 / 13 / 32 mm (1 / 1/2 / 1-1/4")
	<b>Core Bit:</b> 54 mm (2-1/8")	<b>Steel:</b> 13 mm (1/2")
	<b>Wood:</b> 32 mm (1-1/4")	<b>Diamond Core Bit:</b> 65 mm (2-9/16")
	<b>Masonry:</b> 26 mm (1")	<b>Wood (Auger Bit):</b> 32 mm (1-1/4")
	<b>Wood (Self-Feed Bit):</b> 32 mm (1-1/4")	
<b>Blows Per Minute (BPM)</b>	0 - 5,000	
<b>Chuck Capacity</b>	1.5 - 13 mm (1/16 - 1/2")	
<b>Vibration Level</b>	<b>Hammer Drilling into Concrete:</b> 14.	<b>Chiselling:</b> 14 m/s <sup>2</sup>

 Back

 Scroll To Top


DHR263

Model

Detail & Spec	Related Contents	Related Local Models	Related Accessories
<b>Sound Pressure Level</b>	94 dB(A)		
<b>Sound Power Level</b>	105 dB(A)		
<b>Noise K Factor</b>	3 dB(A)		
<b>Dimensions (L x W x H)</b>	350 x 116 x 232 mm (13-3/4 x 4-9/16 x 9-1/8")		
<b>Quick Change Drill Chuck</b>	NO		
<b>Shank Type</b>	<b>Hammer:</b> SDS-PLUS Shank		
<b>Net weight</b>	4.1 - 5.1 kg (9 - 11.3 lbs.)		