


## Accessories

### Chain Saws

#### Guide Bar / Saw Chain / Guide Bar Cover / Drive sprocket

SC: Semi chisel, MC : Micro chisel, FC: Full chisel



Guide Bar				Saw Chain						Bar Cover	Drive sprocket			
Bar length	Motor Mount	Type	Part No.	No.of drive links	gauge	pitch	Type OREGON/DOLMAR	Cutter type	Part No.	Part No.	Type	Part No.		
40cm/16"	K095	Sprocket nose bar	D445040641	66	1.3mm/.050"	.325"	20BP / 082	MC	D523082066	419560-5 D952010640	Rim sprocket .325" SM7-7	D181224040		
33cm/13"	K095	Sprocket nose bar	D445033631	56	1.5mm/.058"	.325"	21BP / 086	MC	D528086656	419559-0 D952010630				
38cm/15"	K095		D445038631	64					D528086664	419560-5 D952010640				
45cm/18"	K095		D445045631	72				D528086672	D952020650					
33cm/13"	K095	Sprocket nose bar	D445033631	56	1.5mm/.058"	.325"	21LP / 686	FC	D534686056	419559-0 D952010630				
38cm/15"	K095		D445038631	64					D534686064	419560-5 D952010640				
40cm/16"	K095		D445140631	66					D534686066	419560-5 D952010640				
45cm/18"	K095		D445045631	72					D534686072	D952020650				
45cm/18"	K095	Sprocket nose bar	D443045661	64	1.3mm/.050"	3/8"	72V / 496	FC	D513496064	D952020640			Rim sprocket 3/8" SM7-7	D026224010
53cm/21"	K095		D443053661	72					D513496072	D952020650				
38cm/15"	K095	Sprocket nose bar	D443038651	56	1.5mm/.058"	3/8"	73DP / 093	SC	D523093656	419560-5 D952010640				
45cm/18"	K095		D443045651	64					D523093664	D952020640				
53cm/21"	K095		D443053651	72				D523093672	D952020650					
53cm/21"	K095	Solid bar	D445053451	72				D523093672	D952020650					
40cm/16"	K095	Sprocket nose bar	445040651	60	1.5mm/.058"	3/8"	73LP / 099	FC	D528099660	D952020640				
45cm/18"	K095		D443045651	64					D528099664	D952020640				
53cm/21"	K095		D443053651	72					D528099672	D952020650				
53cm/21"	K095		Solid bar	D445053451					72	D528099672	D952020650			

#### Rim sprocket system



Pitch	Part No.
.325" SM7-7	181224040 D181224040
3/8" SM7-7	D026224010

#### File and File holder

For Model:  
Chain saw



Saw chain type	Size	File	File and File holder
		Part No.	Part No.
20BP, 21BP, 21LP, 95VP, 082, 086, 686, 484	4.8mm	D953003070	197712-5 D953003070
72V, 73DP, 73LP, 496, 093, 099	5.5mm	953003040	953003040

#### File handle, Flat file & Depth gauge jointer

For all saw chain



File handle	Flat file	Depth gauge jointer
Part No.	Part No.	Part No.
D953004010	D953003060	D953100090

#### Fuel mixture



Size	Part No.
1L	456236-3

#### Chain oil

With Makita chain oil, chain oiling is formulated to adhere to the bar and chain and to reduce wear. Adhesion additive helps keep sap and pitch from clinging to the bar and chain. (Not available in Austria)



Size	Part No.
100ml	182229-1
1L	195093-1 988002656
5L	988002658
55L	988002260
200L	988002261

#### BIOTOP Chain oil

With BIOTOP, chain oiling is safe for environment. BIOTOP is purely vegetable-based and readily biodegradable. It meets the strict requirements of the RAL UZ48 environment mark for environmental compatibility, lubrication, and aging resistance.



Size	Part No.
1L	980008610
5L	980008611
55L	980008217
200L	980008218

#### Steel case



Part No.
821672-6 98895963



### Petrol Chain Saw

### EA5600F 330, 380, 400, 450 mm (13, 15, 16, 18")

- Anti Vibration
- Automatic Oiling
- Chain Brake
- Primer Pump
- Capacitor discharge ignition
- Easy Start

#### Standard Equipment :

Saw Chain, Guide Bar, Guide Bar Cover, Socket Wrench, Slotted screwdriver (country-specific)

<b>Saw chain</b>	Pitch : 3/8" or 0.325" Gauge: 1.3 mm (0.050") / 1.5 mm (0.058")
<b>Displacement</b>	55.7 mL
<b>Engine power</b>	3.0 kW / 4.1 PS
<b>Fuel Tank Capacity</b>	0.6 L
<b>Chain Oil Tank Volume</b>	0.3 L
<b>Sound Pressure Level</b>	104.4 dB(A)
<b>Sound Power Level</b>	116.5 dB(A)
<b>Vibration Level</b>	Front / Rear: 5.5 / 5.0 m/s <sup>2</sup> or less
<b>Dimensions (L x W x H)</b>	430x237x297 mm (17"x9-3/8"x11-5/8")
<b>Net weight</b>	5.8 kg (12.8 lbs.)

Net weight: without Guide bar / Saw chain

Items of standard equipment and specifications may vary by country or area.

weight according to EPTA-Procedure 01/ver.2.1

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201802



## Petrol Chain Saw

EA5600F 330, 380, 400, 450 mm (13, 15, 16, 18")

# 3.0 kW High Power

for Semi-Professionals

Displacement

# 55.7 mL



# 55.7 mL 3.0kW High Power

Stratified air scavenging engine complying with strict exhaust emission regulations



## Centrifugal air cleaner for enhanced air filtration

Centrifugal separation system effectively removes large dust particles away from intake air and reduces dust stuck on the filter to extend intervals of filter maintenance.



- Indicates the direction of the movement of air containing a few dust particles.
- Indicates the direction of the movement of air containing dust particles.

## Excellent air filter system

- Uses PET air filter that features excellent humidity resistance, wet and oil resistance
- Easy to wash with water or using air duster, etc.
- Reduced frequency of the maintenance by increasing surface area of air cleaner



## Captive nuts

prevent loss of nut when removing sprocket cover to replace guide bar or saw chain.



## Touch & Stop switch system

stops the engine with a light touch and returns "on" position automatically to prevent flooding of the carburetor.



## Primer pump

located in a safe concave position, and accordingly protected from damage to be caused by impacts with branches of trees.



## Low-vibration system

Metal spring damping system for reducing vibration.



## Fuel level window

allows to check how much fuel is left in the tank from outside.



## Large combination lever

provides better handling even when wearing gloves.



## Easy Start

Spring-assisted recoil starter reduces user's fatigue by drastic reduction of resistance caused when the starter rope is pulled.



## Anti-icing

