## New 52.5 mL 4-stroke engine



Inakita

BS300TH



#### Improved by 20% in air flow efficiency

Max air velocity

Fan shape has been changed. Air can be pushed out smoothly with less air flow loss. (compared with our current Fan)

Easy-to-pull recoil starter

#### Accessories

Oil bottle set 🧧	Hip belt set
220ml 10W-30	
Part No. 198279-6	Part No. 198645-7
Flat nozzle	Band 25 set
Part No. 196911-6	Part No. 196733-4
End nozzle 90-62	Long pipe 90 set
	makita
Part No. 198034-6	Part No. 197723-0
Short pipe 90 set	Engine maintenance kit M
	Part No. 198282-7
Databa	Air cleaner element set M
Part No. 196912-4	Part No. 198284-3

#### Low vibration for reduced operator stress and fatigue

- Vibration to the back of operator is reduced by the 4 damper springs mounted between the engine and the backpack frame.
- Vibration at the handle is significantly reduced by effectively damping transmission of vibration from the engine to the nozzle.



#### **Comfortable backpack harness**

- Cushioned back padding and shoulder straps are well-ventilated for effective sweat evaporation.
- · Adjustable straps provide a perfect fit for every user.





#### **Petrol Blower** EB5300TH Tube-mounted throttle / EB5300WH Hip-mounted throttle

		EB5
🟓 Anti Vibration	Displacement	52.5 n
	Max Air Volume	15 m³/
D Primer Pump	Max Air Velocity	98 m/
Capacitor discharge ignition	Fuel Tank Capacity	1.8 L (
	Spark plug	NGK C
	Sound Pressure Level	96.0 d
🕖 Auto Decompression	Sound Power Level	102.5
	Vibration Level Right Handle	2.2 m/
	Vibration Level Left Handle	-
	Dimensions	320x4
	$(L \times W \times H)$	(12-5/8
	Net weight	8.9 kg

	EB5300TH	EB5300WH
	52.5 mL	52.5 mL
	15 m³/min (516 CFM)	15 m³/min (516 C
	98 m/s (220 MPH)	98 m/s (220 MF
	1.8 L (61 oz.)	1.8 L (61 oz.)
	NGK CMR6H	NGK CMR6H
	96.0 dB(A)	96.0 dB(A)
	102.5 dB(A)	102.5 dB(A)
2	2.2 m/s <sup>2</sup>	2.3 m/s <sup>2</sup>
	-	0.5 m/s <sup>2</sup>
	320x450x475mm	320x510x475m
	(12-5/8"x17-3/4"x18-3/4")	(17-3/4"x20"x18-3/4
	8.9 kg (19.7 lbs.)	9.1 kg (20.1 lbs.

Standard Equipment :

Oil bottle set, Box Wrench, Driver, Flexible Pipe, Swivel Pipe, Hose Clamp, End nozzle, Flat Nozzle, Long Pipe, Short Pipe, Accessory Bag, Cable Holder Net weight: W/O Fuel & Blower pipe. Overall length: W/O Blower pipe

Items of standard equipment and specifications may vary by country or area. weight according to EPTA-Procedure 01/ver.2.1

### Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

CFM)

PH)

nm



Tube-mounted throttle Hip-mounted throttle



# High power and lightweight

Larger air volume



Max air velocity



Tube-mounted throttle EB5300TH Hip-mounted throttle EB5300WH

