



Petrol Brushcutter EM2500U 24.5mL

Ergonomic handle bar of asymmetrical design.



Designed so that the vertical center line of the handle bar stays aligned with that of user

- Enables user to work in a comfortable posture with less fatigue throughout operation.
- Provides easy handling.



24.5 cm³ 2-stroke engine

Shaft pipe diameter:
24mm (15/16")

Spindle thread size:
M8x1.25, Left-handed

String trimmer head (for grass, light weeds)

* with adapter	Description	Ref.	Part No.
	Manual	-	B-02951
	Bump & Feed	B&F 4L	A-89121
	Bump & Feed	B&F Z5L	A-89143
	Automatic	UltraAuto 4L	*B-02945

Brushcutter blades	Application	Blade dia. / No. of teeth / Thickness	Part No.
Hole Dia.: 25.4mm Triple blade 	for tall, thick grass, scrub and tangled undergrowth	230mm / 3 / 3.0mm	195298-3
Star blade 	for tall grass and scrub	230mm / 4 / 1.8mm	B-14118
Eddy blade 	for thick grass and scrub	230mm / 8 / 1.8mm	B-14130
Saw blade 	for bushes and thin tree trunks Not available in some countries due to local regulation	230mm / 80 / 1.8mm	B-14152
TCT Saw blade 	for gnarled bushes and thin tree trunks Not available in some countries due to local regulation	230mm / 36 / 1.8mm	A-48321

Electronic Ignition Primer Pump

Standard Equipment :

Star blade (4 tooth metal blade), Nylon cutting head, Socket wrench, Hex wrench, Shoulder harness with single shoulder strap, Guard (Protector)

Displacement	24.5mL
Engine power	0.73kW / 1.0PS
Fuel tank	0.4L
Spindle size	M8 x 1.25
Dimensions (L x W x H)	1,770x620x410mm (69-3/4"x24-3/8"x16-1/8")
Net Weight	4.5kg (9.9lbs)

Net weight : without guard, cutting tool, shoulder harness and fuel



Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan