



HR2300

Rotary Hammer

23 mm (7/8") Adapted for SDS-PLUS bits

23 mm (7/8") 2.3 J Rotary Hammer, SDS-PLUS Bits



Standard Equipments:

Side Grip, Depth Gauge

Detail

- 23 mm (7/8") 2.3 J Rotary Hammer, SDS-PLUS Bits
- Easy-to-grip handle ergonomically designed to give maximum power thrust
- 2.3 Joules (EPTA) impact energy delivers high performance
- 2 operation modes - hammering with rotation and rotation only
- Less bit wobbling
- One touch sliding chuck enables quick and easy bit changes
- Variable speed trigger allows operator to adjust speed based on materials or application
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- Operation mode change lever positioned on the bottom of gear housing for reduced possibility of breakage
- Depth gauge for increased drilling consistency
- Side grip with elastomer soft grip

- Double insulated

Note

Spec

Carbon Brush	325	
Continuous Rating Input	720W	
Impact Energy	EPTA-Procedure 05/2009: 2.3 J	Our experimental conditions: 2.6 J
Capacity	Concrete (w/ TCT Bit): 23 mm (7/8")	Concrete (w/ Core Bit): 68 mm (2-11/16")
	Concrete (w/ Diamond Core Bit): 70 mm (2-3/4")	Steel: 13 mm (1/2")
	Wood: 32 mm (1-1/4")	Core Bit: 68 mm (2-11/16")
	Diamond Core Bit: 70 mm (2-3/4")	Masonry: 23 mm (7/8")
	Wood (Auger Bit): 32 mm (1-1/4")	Wood (Self-Feed Bit): 32 mm (1-1/4")
Blows Per Minute (BPM)	0 - 4,600	
Sound Pressure Level	90 dB(A)	
Sound Power Level	101 dB(A)	
Vibration Level	Hammer Drilling into Concrete: 15.5 m/s ²	Drilling: 2.5 m/s ²
Dimensions (L x W x H)	356 x 77 x 209 mm (14 x 3 x 8-1/4")	
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")	
Quick Change Drill Chuck	NO	
Shank Type	Hammer: SDS-PLUS Shank	
Net weight	2.7 - 3.1 kg (5.9 - 6.9 lbs.)	

Power supply cord	2.5 m (8.2 ft)	