

Smooth cutting





Fixed shoe For added durability

Longer 30 mm (1-3/16") stroke

for faster cutting performance

Large 2-finger trigger for added convenience

Soft grip

handle provides increased comfort on the job.

Toolless blade change

for fast blade installation and removal

Accessory

Hook set

allows to hang the machine on ladder rungs or quard rails of aerial work platform. (country-specific)



Part No. 191C05-0











Recipro Saw

Double Insulation Variable Speed

Carrying Case

Standard Equipment: Recipro Saw Blades

JR3051T Continuous Rating Input

Length of Stroke Strokes Per Minute (SPM) Capacity

Vibration Level

Sound Pressure Level

30 mm (1-3/16") 0 - 3,000

Sound Power Level $(L \times W \times H)$ Net weight Power Supply Cord 303

Pipe: 130 mm (5-1/8") Wood: 255 mm (10") Cutting Boards: 19.5 m/s²
Cutting Wooden Beams: 19.5 m/s² 88 dB(A) 99 dB(A) (17-5/8"x3-13/16"x6-15/16") 3.2 - 3.3 kg (7.1 - 7.3 lbs.)

2.5 m (8.2 ft) The weight may differ depending on the attachment(s). The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan