

# **High power Portable Cut-off**



Toolless adjustment of guide plate (LW1400 only)

allows for easy adjustment of the guide plate by simple handling

3 stage position change

0 to 45 degree angle adjustment



Change of saw head locking device from chain lock to pin lock (LW1400 only)

makes it easier to lock down the saw head for storage and transport.





for easy transport to job site



Shaft lock for easy replacement of abrasive cut-off wheel



LW1401

Photo: LW1400



#### Cutting Capacity

D: Diameter

W: Width

Form of	Miter	Miter angle		
materials	<b>0</b> °	45°		
O p	D: ø127mm (2")	D: ø127mm (2")		
← W →     H   H	H x W: 102 x 194mm (4" x 7-5/8") 70 x 233mm (2-3/4" x 9-1/8")	H x W: 115 x 103mm (4-1/2" x 4-1/16")		
k- W->  	H x W: 119 x 119mm (4-11/16" x 4-11/16")	H x W: 106 x 106mm (4-3/16" x 4-3/16")		
STS	S x S: 137 x 137mm, T: 10mm (5-3/8" x 5-3/8", 3/8")	S x S: 100 x 100mm, T: 10mm (4" x 4", 3/8")		

H: Height

S: Side

T: Thickness

#### Accessory

Abrasive cut-off wheel

For all ferrous materials (Steel,cast iron) and other hard metals. These items are available on request. Contact us for the minimum order quantity

Size (mm): 355x3x25.4 Grit: A36P G.F.Q'ty: 1.0G	Per pkg.	Part No.
	5	A-89545-5
	25	A-89545-25
	5	A-89953-5
	5	B-10730-5
	25	B-10730-25
	5	B-10665-5
	25	B-10665-25

Double Reinforced Abrasive cut-off wheel

Size (mm): 355x3x25.4 B-16891-5 Grit: A30P B-16891-25 G.F.Q'ty: 2.0G



### **Portable Cut-off**

Double Insulation

Standard Equipment:

Abrasive Cut-Off Wheel. Socket Wrench (LW1401only)

LVV 1400 / LVV	14U I 355n	nm (14")	
	LW1400	LW1401	
Continuous rating Input	2,200W	2,200W	
Wheel diameter	355mm (14")	355mm (1	4")
Hole dia.	25.4mm (1")	25.4mm (	1")

25.4mm (1") No load speed (rpm) 3,800 3,800 530x295x640mm (20-7/8"x11-5/8"x25-1/4") 500x290x620mm (19-3/4"x11-3/8"x24-3/8") Dimensions Net Weight 17.0kg (37.5lbs) 16.6kg (36.6lbs) 2.5m (8.2ft) Power supply cord 2.5m (8.2ft)

\*weight according to EPTA-Procedure 01/2003

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

203