





## High performance and durability

### Cutting Capacity

Miter angle		0°	45°
Form of materials		ø127mm (5")	ø127mm (5")
		H x W: 102 x 194mm (4" x 7-5/8") 70 x 233mm (2-3/4" x 9-1/8")	H x W: 115 x 103mm (4-1/2" x 4-1/16")
		H x W: 119 x 119mm (4-11/16" x 4-11/16")	H x W: 106 (4-3/16) x 106 (4-3/16)
		S x S: 137 x 137mm, T: 10mm (5-3/8" x 5-3/8", 3/8")	S x S: 100 x 100mm, T: 10mm (4" x 4", 3/8")

\* with Abrasive cut-off wheel 355



Carry handle for easy transportation


Quick release vise



Adjustable guide plate provides three angle settings up to 45° left and right; 15°, 30°, 45°



203 

 Double Insulation

<b>Continuous rating input</b>	2,000W
<b>Wheel Diameter</b>	355 mm (14")
<b>No Load Speed (RPM)</b>	3,800
<b>Dimensions (L x W x H)</b>	500x280x620mm (19-3/4"x11"x24-3/8")
<b>Net weight</b>	14.3 kg (31.5 lbs)
<b>Power supply cord</b>	2.5 m (8.2 ft)

**Standard Equipment:** Abrasive Cut-Off Wheel, Hex Wrench

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan