

# Tool-less blade clamp

(MT450T only)

Blade can be set in place with a single insert and removed simply by turning the blade clamp.



Photo : MT450T

## Dustproof and dripproof design

1. Front side of the slider is protected against saw dust by;
  - (1) Air from the fan that sweeps saw-dust
  - (2) X ring and Felt that seal out saw-dust from the gear room
2. Gear room is protected against water drops by placing a rubber seal ring on the mating surface between Gear housing and Gear housing cover.



Photo : MT450T

Soft grip provides comfortable operation.



Tool-less shoe adjustment enables shoe adjustment by simply pressing the button.



Large trigger switch enables variable speed for accurate cutting.



- Double Insulation
- Variable Speed

<b>Continuous rating Input Capacity</b>	1,010W Pipe : 130mm (5-1/8") Wood : 255mm (10")
<b>Length of stroke</b>	28mm (1-1/8")
<b>Strokes per minute (spm)</b>	0 - 2,800
<b>Dimensions (L x W x H)</b>	MT450T : 457x98x170mm (18"x3-7/8"x6-11/16") MT450 : 457x98x174mm (18"x3-7/8"x6-7/8")
<b>Net weight</b>	MT450T : 3.2kg (7.0lbs) MT450 : 3.1kg (6.9lbs)
<b>Power supply cord</b>	2.0m (6.6ft)

303

### Standard Equipment :

Recipro saw blade (for some countries only), Hex wrench (MT450 only)

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan