

Lightweight, High efficiency



Hex wrench holder

Ergonomically designed barrel grip

Variable speed control by dial



**Lightweight
1.2kg**

Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.

Dust extraction system (Option)

Dust extraction system is available as an option for dust removal in applications with sanding pad.



Part No.199895-7



459

Double Insulation

Variable Speed

Continuous rating input	200W
Oscillations per minute (opm)	15,000-22,000
Vibration Level	Sanding: 2.5 m/s ² Cutting w/ Plunge Cut Saw Blade: 8.0 m/s ² Cutting w/ Segmental Saw Blade: 4.0 m/s ² Scraping: 9.5 m/s ²
Sound Pressure Level	Sanding: 78 dB(A) Cutting w/ Plunge Cut Saw Blade: 79 dB(A) Cutting w/ Segmental Saw Blade: 79 dB(A) Scraping: 78 dB(A)
Dimensions (L x W x H)	283x68x98 mm (11-1/8"x2-11/16"x3-7/8")
Net weight	1.2-1.3 kg (2.7-3.0 lbs.)
Power supply cord	2.0 m (6.6 ft.)

Standard Equipment: Hex Wrench

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan