V-notch in base plate helps easy tracing of cutting line.



Dust collector

catches dust that drops through the base of base cover.

Dust connector assembly

connectable to vacuum cleaner.

LED job light

brightly illuminates the cut line for easy cutting of workpiece in the dark place.



Cutting depth adjustment



- Cutting depth can be adjusted to drywall thickness.
- Prevent accidental breakage of wires

Blade cover

protects drywall surfaces from damage/ scratches.







Blades



10.8V Li-ion batteries

Compatible with both special blades for this drywall saw and option snap-off blades.

Li-ion Battery & Charging Time Reference



Cordless Drywall Saw SD100D

Variable Speed

Orbital Cutting

Dust Collecting

Built-in Job Light

Carrying Case

Strokes Per Minute (SPM) 0 - 6,000 Length of Stroke 6 mm (1/4") Capacity Drywall: 30

Capacity Drywall: 30mm (1-3/16")
Wood: 15 mm (9/16")

Max Output 260W

Vibration Level Cutting Drywall (thickness 30mm): 3.0 m/s²
Cutting Chip Board (thickness 15mm): 5.5 m/s²

 Sound Pressure Level
 77 dB(Å)

 Dimensions (L x W x H)
 239x79x266mm (9-3/8"x3-1/8"x10-1/2")

 Net weight
 BL1015 / BL1020B: 1.5 kg (3.3 lbs)

 BL1040B: 1.6kg (3.6lbs)

Standard Equipment: Blade, Blade cover, Base cover, Hex Wrench, Battery, Charger

weight according to EPTA-Procedure 01/ver.2.1 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



