



# **Cordless Impact Driver** TD091DZ





Tool does not come with Phillips bit.

**Extra Lightweight Comfort** 

## **High durability**

achieved by Motor, switch and Impact section in consideration of high frequency fastening of machine screws.

Max. fastening torque

90N.m (800in.lbs)

Lightweight at

0.87kg (1.9lbs)

#### Extra compact design with a short overall length of 134mm (5-1/4")

achieved by employing 4-pole motor

Trakita





#### **Battery power reduction** warning lamp

Indication lamp blinks to warn operator visually of battery power reduction.




#### **Automatic battery** shut-off system

If battery power reduces further, the motor automatically stops to avoid incomplete fastenings.

In compliance with EMC standards (for some countries only)








minimizes operator's hand and finger fatigue in long, continuous operation in assembly and manufacturing applications.

Variable speed control by trigger











**Charger DC10WA** approx. 50 minutes charging time



#### Cordless Impact Driver

Variable Speed



Reversing



Standard Equipment: Battery and Charger are sold separately.

(Tool does not come with Phillips bit.) \*weight according to EPTA-Procedure 01/2003

#### **TD091DZ**

Capacity

Machine screw: M4 - M8 (5/32" - 5/16") Standard bolt: M5 - M12 (3/16" - 1/2") High tensile bolt: M5 - M10 (3/16" - 3/8") Coarse thread (in length): 22 - 90mm (7/8" - 3-1/2")

Impacts per minute (ipm) No load speed (rpm) Max. fastening torque Dimensions (L x W x H)

0-2.400 90N.m (800in.lbs)

0-3,000

134x54x200mm (5-1/4"x2-1/8"x7-7/8") 0.87kg (1.9lbs)

Net Weight

Items of standard equipment and specifications may vary by country or area.

### Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan