

Cordless Hedge Trimmer Series






Optimum blade shape for smooth cutting of thin branches

Sharp edge curve Blade

UH004G

600 mm (23-5/8")



High/ Med/ Low Model: UH004G / Battery: BL4040

85/160/370 min

Optimum for rough cutting of thick branches

Sharp edge Blade

UH006G 600 mm (23-5/8")

UH007G 750 mm (29-1/2) Maximum branch diameter

Strokes per minute High speed mode (No load speed) 5,000 min⁻¹

Standard Blade

UH008G 600 mm (23-5/8")

UH009G 750 mm (29-1/2"

25.0 mm











40Vmax series movie



40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

BL motor provide high power and excellent cutting performance







5 position rotating rear handle




Twigs are caught easily and held firmly Sharp edge curve Blade / Sharp edge Blade UH006G / UH007G UH004G / UH005G



Reverse rotation system

release the blade when it is jammed by thick



Optimum blade shape for smooth cutting Sharp edge curve Blade UH004G / UH005G



3-speed







NEW Chip receiver

can make it easier for user to collect leaf and twig debris, thanks to:

- lower height of the connecting hooks
- reduced step height of the edge of the chip catching plate





High water-resistance allows to operate the




eXtreme Protection Technology

Enhanced Dust and **Drip-proof Performance** ensure reliable operation even under bad weather



Accessories



Charging Time Reference

40VIIII	DC40RA [251CS/rghg]	DC40RC
*1 BL4020 2.0Ah	22 _{min}	30 _{min}
*1 BL4025 2.5Ah	28 _{min}	38 _{min}
*1 BL4040 4.0Ah	45 _{min}	67 _{min}
BL4050F 5.0Ah	50min	85min
*1 Recommended battery		•

Cordless Hedge	Trimmer	UH004G, U	H005G, UH0	006G, UH00	7G, UH008G	, UH009G	
M		UH004G	UH005G	UH006G	UH007G	UH008G	UH009G
Marake Brake	Blade Length	600 mm (23-5/8")	750 mm (29-1/2")	600 mm (23-5/8")	750 mm (29-1/2")	600 mm (23-5/8")	750 mm (29-1/2")
Reversing Strok	Max Cutting Capacity	23.5 mm (15/16")	23.5 mm (15/16")	25.0 mm (1")	25.0 mm (1")	21.5 mm (7/8")	21.5 mm (7/8")
	Strokes Per Minute	High / Mid / Low:	High/Mid/Low:	High/Mid/Low:	High/Mid/Low:	High / Mid / Low:	High / Mid / Low:
	(SPM)	5,000/3,600/2,000	5,000/3,600/2,000	4,000 / 3,000 / 2,000	4,000/3,000/2,000	5,000 / 3,600 / 2,000	5,000 / 3,600 / 2,000
	Sound Pressure Level	85 dB(A)	86 dB(A)	81 dB(A)	81 dB(A)	82 dB(A)	83 dB(A)
	Sound Power Level	96 dB(A)	97 dB(A)	92 dB(A)	92 dB(A)	93 dB(A)	94 dB(A)
Constant Speed	Vibration Level	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:
		2.9 / 2.5 m/s ² or less	3.1/2.7	$3.0/2.5 \text{m/s}^2 \text{or less}$	3.4/3.1	$3.1/2.5 \text{ m/s}^2 \text{ or less}$	3.2/2.5
	Dimensions	w/BL4020/BL4025:	w/BL4020/BL4025:	w/BL4020/BL4025:	w/BL4020 / BL4025:	w/BL4020/BL4025:	w/BL4020/BL4025:
7 trei violation	(L x W x H)	1,120 x 223 x 191 mm	1,263 x 223 x 191 mm	1,123 x 223 x 191 mm	1,274 x 223 x 191 mm	1,120 x 223 x 191 mm	1,262 x 223 x 191 mm
		(44 x 8-3/4 x 7-1/2")	(49-3/4 x 8-3/4 x 7-1/2")	(44-1/4 x 8-3/4 x 7-1/2")	(50-1/4 x 8-3/4 x 7-1/2")	(44 x 8-3/4 x 7-1/2")	(49-3/4 x 8-3/4x 7-1/2")
	Net weight	4.3 - 4.9 kg (9.5 - 10.8 lbs.)	4.5 - 5.1 kg (9.9 - 11.2 lbs.)	4.4 - 5.0 kg (9.7 - 11.0 lbs.)	4.6 - 5.2 kg (10.1 - 11.5 lbs.)	4.3 - 4.9 kg (9.5 - 10.8 lbs.)	4.4 - 5.0 kg (9.7 - 11.0 lbs.)

The weight does not include accessories but battery cartridge(s). The lightest and heaviest combination weight of the appliance and battery cartridge(s) are shown in the table. Items of standard equipment and specifications may vary by country or area.

Standard Equipment: Blade Cover, Safety Goggles (country-specific), Chip Receiver, Battery, Charger

Makita Corporation