
Telescopic pipe shaft adjustable in length from 845mm (33-1/4") to 1,195mm (47")

(with Nylon cord)


Easy lock lever



Ergonomic loop handle for added maneuverability

- Provides easy handling especially on level ground.
- Tool-less removal/installation
- Installation position is adjustable to any desired position without tool.





Well balanced design with fully adjustable features to suit any operator





· reduces the risk of damaging fences, flowers or ornaments.





Clockwise direction

When a right hander uses the machine, grass clippings fly toward the opposite side of the person.

Storage for Spare plastic blade



Excellent Mobility





Extreme Protection Technology

Enhanced dust and drip-proof performance for use in bad weather

■ Work amount (min)

on a single full battery charge

Tronk amount ()				
	Cutting blade	Battery NEVinax NATIONAL STATES	No load	With load*
	with Nylon cord diameter : ø1.65 mm ø260mm (One String comes out from opening)	BL1016 1.5Ah	15	8
		BL1021B 2.0Ah	19	10
		BL1041B 4.0Ah	38	21
	with Plastic blade	BL1016 1.5Ah	21	10
	Trimming width: ø230mm	BL1021B 2.0Ah	28	13
	(One-blade cutter)	BL1041B 4.0Ah	55	26

*Depends on the density of weeds

Cordless Grass Trimmer UR100D

Cutting Width	Nylon Cutting Head : 260 mm (10")
	Plastic Blade : 230 mm (9")
No Load Speed	10,000
(RPM)	
Spindle Size	M8 x 1.25 RH
Sound pressure lev	el Nylon Cutting Head : 74 dB (A)
	Plastic Blade : 75.8 dB (A)
Vibration emission	Front / Rear: 2.5 m / 2.5 m/s ² or less
Dimensions	Nylon Cutting Head: 845-1,195x267x210-315(33-1/4"-47"x10-1/2"x8-1/4"-12-3/8")
(L x W x H)	Plastic Blade: 852-1,202x267x210-315(33-1/2"-47-1/4"x10-1/2"x8-1/4"-12-3/8")
Net weight	1.9 - 2.1 kg (4.3 - 4.6 lbs.)
	LIP100DW/VE: 2 hatton/1 EAh chargor

Soft Start UR100DZ:

Battery & charger not include

Standard Equipment:
Wire guard (327065-0), band assembly (125516-5), hex. Wrench 4 (783202-0), accessory bag (831304-7), nylon cord 1.65-15m set M (198859-8)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

A4-052023-1

CÔNG TY TNHH MAKITA VIỆT NAM NO 454, Block 16, 181.12 Đượng số 3, KCN YSP U, P, Hoà Phú, TP, Thú Đầu Mặt, Bình Dượng ĐƯ, CO274 362 8339 - Fac 10274 362 8339 - Website: www.makita.com.um

CHI NHÁNH CTY TNHH MAKITA VN TAI MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG Kho 5, Số 1, Đường Số 6, KCN - ĐT - DV VSIP Bắc Ninh, P. Phù Chẩn, TP. Từ Sơn, T. Bắc Ninh. ĐT: 0222 376 5942 Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI 65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội. 9T: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

CHI NHÁNH BUÔN MA THUỘT 68 Lê Đức Thọ, P. Tháng Idi, TP. Buôn Ma Thuột, T. Đák Lák. TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

CHI NHÁNH NHA TRANG Ló 3638 đượng BB, Khu đó thị Vinh Điệm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa ĐT: 0258 220 0039 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh. DT: 0283 821 5191









