### No load speed: 800 min.<sup>-1</sup>

providing high efficiency fastening.

#### Compatible with variable sockets with socket adapter





Socket adaptor 9.5 mm (3/8') Part No.191A50-3



Socket adaptor 6.35 mm(1/4')Part No.191A51-1




The grip diameter is smaller than that of the competitors, providing the same good handling as hand ratchet wrenches.



Can also be used as a hand ratchet wrench

Forward / reverse rotation change

Turn the reversing lever to the A side for clockwise rotation or to the B side for counterclockwise rotation.



#### Li-ion Battery & Charging Time **Reference, Compatibility Chart**



Able to tighten 13mm nut onto M8 threaded rod





Switch lever

with preglow and afterglow functions

EXTREME PROTECTION TECHNOLOGY

nin de





**Standard Equipment** Tool bag Part No. 832071-7



| Cordless Ratchet Wrench                |   |  |
|--|---|--|
| WR100D 9.5 mm (3/8") / 6.35 mm (1/4 ") |   |  |
| Wariable Speed                         | Capacity                                | Standard Bolt: M5 - M12 (3/16" - 1/2")<br>High Tensile Bolt: M5 - M10 (3/16" - 3/8")                           |
| Marke Brake                            | Square Drive<br>No Load Speed (RPM)     | 9.5 / 6.35 mm (3/8" / 1/4")<br>0 - 800   |
| Reversing                              | Max Fastening Torque<br>Max Output      | 47.5 N·m (420 in.lbs.)<br>250 W  |
|  | Vibration Level<br>Sound Pressure Level | 2.5 m/s <sup>2</sup> or less<br>74 dB(A)   |
| Carrying Case                          | Dimensions (L x W x H)                  | w/ BL1016/BL1021B: 341x67x63 mm (13-7/16"x2-5/8"x2-1/2")<br>w/ BL1041B: 341x67x84 mm (13-7/16"x2-5/8"x3-5/16") |
|  | Net weight                              | 1.0 - 1.2 kg (2.3 - 2.7 lbs.)  |
|  |   |  |

Standard Equipment : Socket Adapter, Battery, Charger, Tool bag

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combinations, according to EPTA-Procedure 01/2014, are shown in the table Items of standard equipment and specifications may vary by country or area.

Satisfy Professional's Needs

XTE



# Cordless Ratchet Wrench WR100D 9.5 mm (3/8") / 6.35 mm (1/4 ")

Max fastening torque 47.5<sub>N·m</sub>

## **Cordless ratchet wrench powered** by 12V max CXT Li-lon battery

makita





Can also be used as a hand ratchet wrench

