



40Vmax
mechanism
movie



This movie was filmed
in Japan.
Models and specs may
vary by country.

Satisfy Professional's Needs



Cordless Grass Trimmer
UR012G

Accessories ● Standard equipment

Chisel blade
Part No. 199872-9
Blade dia.: 225mm



Protector 225 set MG
Part No. 199873-7



Shredder blade
Part No. 199874-5
Blade dia.: 270mm



Protector set MG
Part No. 199875-3



Trimmer head

Part No. 196324-1
Cord/Line : 2.4mm x3.6m
Ref. : UN-74L

Part No. 197296-3
Cord/Line : 2.0mm x3m
Ref. : ECO 4L

Part No. 199884-2 ●
Cord/Line : 2.7mm
Ref. : 105-M10L

Part No. 191D93-3
Cord/Line : 2.4mm
Ref. : 121-M10L

Part No. 191D89-4
Cord/Line : 2.0mm x4m
Ref. : 96-M10L

Part No. 198893-8 (EU)
Cord/Line : 2.0mm x3m
Ref. : 95-M10L

Part No. 198266-5
Cord/Line : 2.4mm x6m
Ref. : UN-72L

Part No. 199885-0
Cord/Line : 2.0mm
Ref. : 105-M10L

Part No. 199885-0
Cord/Line : 2.0mm
Ref. : 105-M10L

Part No. 191D91-9
Cord/Line : 2.4mm x3m
Ref. : 96-M10L

Part No. 191D91-9
Cord/Line : 2.4mm x3m
Ref. : 96-M10L

Part No. 191D91-9
Cord/Line : 2.4mm x3m
Ref. : 96-M10L



Four-leaf Spiral Nylon cord

Green	Orange	Red
Size	Size	Size
2.0mmx15m	2.4mmx15m	2.7mmx15m
2.0mmx30m	2.4mmx30m	2.4mmx30m
2.0mmx160m	2.4mmx120m	2.4mmx180m
2.0mmx280m	2.4mmx180m	

Protection guard for brush cutting blades

Part No. 191B54-1



Brushcutter blade

Blade dia	2-tooth blade	3-tooth blade	4-tooth blade
255mm	198345-9	195299-1	196895-8
305mm	195624-6 ●	195300-2	-

Plastic blade

Blade dia	Plastic blade Set	Replacement plastic blade
255mm	198383-1	198426-9
305mm	199868-0 ●	199870-3

Shoulder strap assembly

Comfort
Part No. 122A37-4 ●



Charging Time

	DC40RA Fast Charging	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 min	38 min
BL4040 4.0Ah	45 min	67 min
*BL4050F 5.0Ah	50 min	85 min

*1 Recommended battery

Cordless Grass Trimmer

UR012G

Variable Speed	Cutting Width	Metal Blade: 305 mm (12") Chisel Blade: 225 mm (8-7/8") Nylon Cutting Head: 480 mm (18-7/8") Shredder Blade: 270 mm (10-5/8") Plastic Blade: 305 mm (12")
Brake	No Load Speed (RPM)	Metal Blade (3 / 2 / 1): 0 - 6,800 / 0 - 5,000 / 0 - 3,500 Nylon Cutting Head (3 / 2 / 1): 0 - 5,000 / 0 - 4,200 / 0 - 3,500
Reversing	Spindle Size	M10 x 1.25 LH
Electronic 3-Speed	Sound Pressure Level	4-Tooth Blade: 84.3 dB(A) / Plastic Blade: 82.9 dB(A) / Nylon Cutting Head: 79.9 dB(A)
Constant Speed	Sound Power Level	4-Tooth Blade: 97.9 dB(A) / Plastic Blade: 92.4 dB(A) / Nylon Cutting Head: 91.6 dB(A)
Soft Start	Vibration Level	Left / Right: 2.5 / 2.5 m/s ² or less
	Dimensions (L x W x H)	w/ BL4050F: 1,829 x 680 x 590 mm (72 x 26-3/4 x 23-1/4")
	Net Weight	8.0 - 9.3 kg (17.6 - 20.5 lbs.)

Standard Equipment: Cutter blade 205(195624-6), trimmer head 105(199884-2), blade cover (422818-3), hex wrench 4(783202-0), hex wrench 5(783217-7), plastic blade 305 set MG(199868-0), box wrench (782238-6), safety goggles (195246-2), accessory bag (831304-7), band assembly (122A37-4).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

IA4-052023-1



As powerful as 40mL petrol grass trimmer



Wet Guard

Max Output
2.0 kW



CÔNG TY TNHH MAKITA VIỆT NAM

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - DT - VSP Bắc Ninh, P. Phú Châu,
TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG
102 Trưng Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng,
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ
366 Võ Văn Kiệt, Khu Vực S. P. An Thới, Q. Bình Thủy,
TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH BUỒN MA THUỘT
58 Lê Đức Thọ, P. Thắng Lợi, TP. Buon Ma Thuột, T. Đắk Lắk,
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG
Số 01 Lê Duẩn, Dũ An Hoàng Huy Riverside, P. Thượng Lý,
Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHÀ TRẢNG
Lô 36-38 đường B8, Khu đô thị Vĩnh Diễm Trung, Xã Vĩnh Ngọc,
TP. Nhà Trảng, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191



High power and large cutting width of 480mm similar to 40mL class engine grass trimmers



Compatible with a variety of blades

Metal blade	ø305mm
Plastic blade	ø305mm
TCT saw blade	ø255mm
Chisel blade (A specially designed protector is necessary.)	ø255mm
Nylon cutting head (The cutting cord is ø2.7mm quiet type.)	ø480mm
Shredder blade (A specially designed protector is necessary.)	ø270mm

Chisel blade 225 set MG

For brush and thin tree trunks and new growth. Not available in some countries due to local regulation

Part No. 199872-9

Protector 225 set MG

Part No. 199873-7



Shredder blade 270 set MG

for thick grass, scrub and vines

Part No. 199874-5

Protector set MG

Part No. 199875-3



Multi functional control panel: near right hand position for easy access and operation



Reverse button



Reverse switch for clearing entangled weeds and grass from cutting head

Low noise level
96 or lower dB(A)
with ø480mm nylon cutting head

Max Output
2.0 kW



- Enabling user to work with less fatigue even in long continuous operation.
- Allowing for a wider swing.

Run Time (BL4050F x2)*			
Metal blade	High	Med	Low
	85	135	249 min
Nylon cutting head	High	Med	Low
	22	42	106 min

*on a single full battery charge / No load



High water-resistance allows to operate the machine even if it is wet with water.



eXtreme Protection Technology
Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather




Rear end mounted motor
Makes the tool weight balance similar to engine grass trimmers, enabling user to easily lift up the saw head for ridge weed removal, etc.



Automatic torque Drive Technology

Automatically changes the cutting speed according to grass density.



Active Feedback sensing Technology

Torque limiter turns the motor off if the tool is suddenly forced to lock

