40Vmax series



40Vmax mechanism



This movie was filmed in Japan. Models and specs may vary by country.

### Portable Power Pack

Powered by up to four 18V LXT batteries





### **PDC1200**

Powered by 36V-40Vmax built-in battery







Portable power pack and Product on 40Vmax XGT platform

### Adapter set (40Vmax)





### Accessories

### **Trimmer head**

Part No. 196324-1 Cord/Line: 2.4mm x3.6m Ref.: UN-74L

Part No. 198266-5 Cord/Line: 2.4mm x6m Ref.: UN-72L



Part No. 197296-3 Cord/Line: 2.0mm x3m Ref.: ECO 4L



Part No. 191D91-9 Cord/Line: 2.4mm x3m

Part No. 191D89-4

Cord/Line: 2.0mm x4m

Ref.: 96-M10L



Part No. 198893-8 (EU) Cord/Line: 2.0mm x3m Ref.: 95-M10L

### **Brushcutter blade**

For UR006G / UR007G

		2-tooth blade	3-tooth blade	4-tooth blade
_	Blade dia	Ti-		121
	230mm	197997-3	195298-3	195150-5
	255mm	198345-9	195299-1	196895-8

### **Plastic blade**

Cutting width	Plastic blade Set	Replacement plastic blade	
255mm	198383-1	198426-9	
305mm	199868-0	199870-3	

### Four-leaf Spiral Nylon cord

Green		Orange	
Size	Part No.	Size	Part No.
2.0mmx15m	197472-9	2.4mmx15m	198501-1
2.0mmx30m	197473-7	2.4mmx30m	198502-9
2.0mmx160m	197474-5	2.4mmx120m	198503-7
2.0mmx280m	197475-3	2.4mmx180m	198504-5

### Protection guard for brush cutting blades

Part No. 191B54-1 UR006G / UR007G







### Shoulder strap assembly

Part No.122906-3



UR008G: 5.0 - 5.6 kg (11.0 - 12.4 lbs.)

Cover (for the product with metal blade), Accessory Bag, Hex Wrench, Box Driver (UR006G / UR007G), Shoulder Belt, Battery, Charger



### **Charging Time Reference**

40V/122000	DC40RA  Fast Charging	DC40RC
<b>BL4020</b> 2.0Ah	22 <sub>min</sub>	30 <sub>min</sub>
*1 <b>BL4025</b> 2.5Ah	28 <sub>min</sub>	38 <sub>min</sub>
*1 <b>BL4040</b> 4.0Ah	45min	67min
*1 <b>BL4050F</b> 5.0Ah	50min	85min

#### Metal Blade: 255 mm (10") (UR006G / UR007G only) Wariable Speed Nylon Cutting Head: 430 mm (17") Plastic Blade: 305 mm (12") Metal Blade (3/2/1): 0 - 7,000/0 - 5,500/0 - 4,600 **Brake** No Load Speed (RPM) Nylon Cutting Head (3/2/1):0-5,500/0-5,000/0-4,600 Plastic Blade (305 mm) (3/2/1):0-7,000/0-5,500/0-4,600 M10 x 1.25 LH Electronic 3-Speed w/o Cutting Tool, w/ BL4050F: UR006G: 1,840 x 681 x 563 mm (72-1/2 x 26-3/4 x 22-1/4") UR007G: 1,840 x 400 x 269 mm (72-1/2 x 15-3/4 x 10-5/8") UR008G: 1,828 x 227 x 301 mm (72 x 8-15/16 x 11-7/8") Constant Speed Soft Start UR006G: 5.6 - 6.2 kg (12.3 - 13.7 lbs.) UR007G: 5.2 - 5.8 kg (11.5 - 12.9 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Cordless Grass Trimmer** 

UR006G / UR007G / UR008G

### Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202105



Cordless Grass Trimmer UR006G / UR007G / UR008G





### As powerful as 30cc petrol grass trimmer



**Max Output**  $1.0 \, \mathrm{kW}$ 



Standard Equipment: Safety Goggles, Metal Blade (UR006G/UR007G)/Nylon Cutting Head/Plastic Blade (country-specific), Blade \*1 Recommended battery



# High power as 30cc engine tool





### **Rear end mounted motor**

Makes the tool weight balance similar to engine grass trimmers, enabling user to easily lift up the saw head for ridge weed removal, etc.



# **ADT**

## Automatic torque Drive Technology


Automatically changes the cutting speed according to grass density.



# **AFT**

### Active Feedback sensing Technology

Torque limiter turns the motor off if the tool is suddenly forced to lock



### Multi functional control panel: near right hand position for easy access and operation



### **Reverse button**





Reverse switch for clearing entangled weeds and grass from cutting head

Max Output

1.0 kW



Cutting width: 430mm (17") similar to 30mL class engine grass trimmers.

### Protector ( UR006G / UR007G )

by attaching Extension.

• Cutting width: 255mm with Metal blade 430mm with

• Dual-purpose protector, Nylon cutting head can be used

 Cutting width: 255mm with Metal blade 430mm with Nylon cutting head

### Toolless handle lock mechanism for good portability ( UR006G only )





# The vertical center line of the handle bar always stays aligned with that of user ( UR006G only )



- Enabling user to work with less fatigue even in long continuous operation.
- · Allowing for a wider swing.

### New tool-less quick fastening handle holder ( UR006G only )



- Compatible with two-piece handle bar
- Each handle-to-shaft angle is independently adjustable without tool.

# UR007G Loop-Handle

### UR008G Loop-Handle

Nylon Cutting Head and Plastic Blade only



### Protector (UR008G)

- Designed exclusively for use with Nylon cutting head.
- $\bullet \ Narrow \ design \ for \ wide \ working \ field$
- Cutting width: 430mm

### Run Time\*

Nylon cutting head

High Med Low 12 / 24 / 38 min with BL4050F

\*on a single full battery charge / No load