





Max Run Time

45 min

Battery: BL1830B on a full battery charge / No load

Cutting Width

260 mm



Lightweight for reduced operator fatigue

Telescopic shaft pipe

- Well balanced design with fully adjustable features to suit any operator
- Adjustable in length from 1,248mm to 1,436mm.





can be more conveniently locked/released by changing the mechanism from the rotary type to the lever type.

Easy-to-operate front grip

Adjustable to a desired height by changing the angle and position.



Angle adjustment of motor head

The cutting angle can be adjusted in 5 steps.



Edger function

Using the grass trimmer as an edger is suitable for cutting the grass growing along the bricks or blocks.



The nylon cutting head has a bump and feed mechanism







ø1.65mm four-leaf



Accessories

Spool set MG

Part No. 191Y39-5



Four-leaf nylon cord

I

Blue	
Size	Part No.
Ø1.65mmx15m	E-01731
Ø1.65mmx30m	E-01747
Ø1.65mmx445m	E-01753

Charging Time

DC18RC	DC18SD
15 min	30 min
24 _{min}	45 min
22 min	60 min
36 min	90 min
45 min	110 min
55 min	130 min
	15 min 24 min 22 min 36 min 45 min

Cordless Grass Trimmer

DUR193		
Cutting Width	Trimmer Head: 260 mm (10-1/4")	
No Load Speed (RPM) Max Run Time (min)	7,800 w/BL1830B: 45	
Sound Pressure Level	73.2 dB(A)	
Sound Power Level	83.1 dB(A)	
Vibration Level	Left / Right: 2.5 / 2.5 m/s ² or less	
Dimensions (L x W x H)	w/Nylon Cutting Head, w/BL1815N/BL1820B	
	: 1,238 - 1,427 x 265 x 358 mm (48-3/4 - 56-1/4 x 10-3/8 x 14-1/8")	
	w/ Nylon Cutting Head, w/ BL1830B / BL1840B /	
	BL1850B / BL1860B	
	: 1,248 - 1,436 x 265 x 358 mm	
	(49-1/4 - 56-1/2 x 10-3/8 x 14-1/8")	
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)	
Standard Equipment : Safety Goggles (country-specific), Shoulder Belt, Nylon Cord, Battery, Charger		

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan