







## Flexible hose










Part No. 1910C7-9













45 min

**50** min

**BL4050F** 5.0Ah \*1 Recommended battery

\*1 BL4040 4.0Ah

#### Nozzle assembly For rug / carpet Part No.

198525-7 (EU) 198528-1
198523-1
(EU) 198527-3
108526-5



## (EU) 198529-9

#### Flexible hose



#### Crevice nozzle 415

(EU) 198547-7



Filter H set

**HEPA** filter

**CL002G** 

Paper bag ty One touch sw

Part No. 1910C9-5

#### Nozzle assembly For floor Part No. 123486-2





#### Snow-white **Sheet Nozzle**



Part No.







Cyclone unit set

Part No.

#### Straight pipe with pipe lock Part No.

459353-8

Long sash nozzle

198919-6

198990-0

198992-6











#### Compatible model: CL001G, DCL280F, DCL281F, DCL180, DCL181F, DCL140

pe	60
tch	1
	al –

-	Capacity	730 mL
(CPE)		
12.38	Continuous use	w/BL4025, Mode 1/2/3/4
100		:80/40/25/16 min
2.0	Max air flow	1.2 m³/min
47	Max sealed suction	21 kPa (2,100 mmH₂O)
//	Suction power	Mode 1/2/3/4: 20/45/70/125 W
d	Noise level	Mode 1: 54 dB(A)
7	Dimensions (L x W x H)	w/ Pipe & Nozzle, w/ BL4020 / BL4025:
		1,066 x 113 x 152 mm (42 x 4-7/16 x 6
		w/ Pipe & Nozzle, w/ BL4040: 1,081 x 1
		158 mm (42-1/2 x 4-7/16 x 6-1/4")
	Net weight	1.7 - 2.3 kg (3.7 - 5.1 lbs.)

	CL001G	CL002G
apacity	730 mL	Cloth dust bag: 500 mL
		Paper dust bag: 330 mL
ontinuous use	w/BL4025, Mode 1/2/3/4	w/BL4025, Mode 1/2/3/4
	:80/40/25/16 min	:80/40/25/16 min
ax air flow	1.2 m³/min	1.2 m³/min
ax sealed suction	21 kPa (2,100 mmH₂O)	21 kPa (2,100 mmH₂O)
iction power	Mode 1/2/3/4: 20/45/70/125 W	Mode 1/2/3/4: 20/45/70/125 W
oise level	Mode 1: 54 dB(A)	Mode 1: 54 dB(A)
mensions (L x W x H)	w/ Pipe & Nozzle, w/ BL4020 / BL4025:	w/ Pipe & Nozzle, w/ BL4020 / BL4025:
	1,066 x 113 x 152 mm (42 x 4-7/16 x 6")	1,066 x 114 x 152 mm (42 x 4-1/2 x 6")
	w/ Pipe & Nozzle, w/ BL4040: 1,081 x 113 x	w/ Pipe & Nozzle, w/ BL4040: 1,081 x 114 x
	158 mm (42-1/2 x 4-7/16 x 6-1/4")	158 mm (42-1/2 x 4-1/2 x 6-1/4")
et weight	1.7 - 2.3 kg (3.7 - 5.1 lbs.)	1.8 - 3.0 kg (4.0 - 6.6 lbs.)

#### **Cordless Cleaner**

#### CL003GZ03/CL003GZ09/CL003GZ14

<b>4</b> Electronic 4-Speed
<b>≣</b> ○ Built-in Job Light

Capacity Continuous use Max air flow

w/BL4025, Mode 1/2/3/4:80/40/25/16 min 1.0 m³/min 

 Max sealed suction
 20 kPa (2,000 mmH<sub>2</sub>O)

 Suction power
 W/Easy shake off filter EX, Mode 1/2/3/4: 15/35/60/100 W

 Noise level
 Mode 1/2/3/4: 54/59/62/65 dB(A)

 Dimensions (L x W x H)
 w/Pipe & Nozzle, w/BL4020/BL4025

: 1,106 x 113 x 177 mm (43-1/2 x 4-7/16 x 7") w/ Pipe & Nozzle, w/ BL4040 : 1,121 x 113 x 177 mm (44-1/4 x 4-7/16 x 7") 1.9 - 2.5 kg (4.2 - 5.5 lbs.)

Standard Equipment: Filter H set (1910C9-5 \*1\*2\*3 ), nozzle assembly (127827-4\*1, 127828-2 \*2, 127825-8 \*3), sash nozzle (413859-0\*1, 413809-5 \*2, 413770-6 \*3), nozzle holder (459355-4\*1, 459038-6 \*2, 459354-6 \*3), pipe (459356-2\*1, 458942-6 \*2, 459353-8 \*3

The weight does not include accessories but battery cartridge. The lightest and heavies

#### CÔNG TY TNHH MAKITA VIÊT NAM (No 458, Block 16, 181.? Bloong ali 3, KON VSP IL, P. Hoa Phil, TP. Thil Dais Met. Ben Dating BT: 0274 302 8338 - Fax: 0274 302 8339 - Website: www.makita.com.um

Net weight

CHÍ NHÁNH CTY TNHH MAKÍTA VN TAÍ MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG Kho 5, Số 1, Đường Số 6, KCN - ĐT - DV VSIP Bác Ninh, P. Phú Chấn, TP. Từ Sơn, T. Bác Ninh. ĐT: 0222 376 5942 Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NÔI

**67** min

**85** min

CHI NHÁNH ĐÀ NẮNG 102 Triệu Nữ Vương, P. Hải Châu 2, O. Hải Châu, TP. Đà Nắn TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH BUÔN MA THUỘT 68 Lẽ Đức Thọ, P. Tháng lợi, TP. Buôn Ma Thuột, T. Đák Lák, 9T: 0262 355 4556 Fax: 0262 355 4557 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

CHÍ NHÁNH NHA TRANG Lỗ 36:38 đường Bộ, Khu độ thị Vinh Điềm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa ĐT: 0258 220 0039 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

Satisfy Professional's Needs



# Cordless Cleaner CL003G







**CL003G** 
















#### **New cyclone unit**

Filter clogging is suppressed by separating fine dust particles from the air with centrifugal force in the cyclone unit.

Thus, the decrease in suction power of the cleaner is minimized.

The amount of dust that can be sucked until filter needs to be cleaned is about 6 times of dust amount suctioned without cyclone unit.





Easy disposal of the fine dust collected in dust case





For increased cleaning efficiency, the integrated cyclone unit is positioned above the extension pipe so that it does not hit the floor or surrounding objects when cleaning narrow spaces such as the floor under racks or sofas.





#### 4-mode suction power selection with mode memory function

- · The cleaner can memorize a previous power mode and resume vacuuming at the same mode as last time user turned off for user convenience.
- Power mode can be selected before the cleaner is turned on.
- · Selected power mode is indicated by 4 green LEDs.





### Continuous use on a full battery charge Mode 4 3 2 1 16 25 40 80 Battery: BL4025

#### Max sealed suction

CL003G **21**<sub>kPa</sub>

Predecessor Model 8.2 kPa



#### **Redesigned Floor/ Carpet T-nozzle**

- Redesigned structure reduces the resistance caused by suction, providing smooth running.
- Redesigned inside air flow path reduces the noise made inside the nozzle.



#### Pipe locking mechanism

Pipe is fixed with the locking mechanism to prevent it from accidentally coming off.





#### Single LED job light

Easy filter setting

Filter can be fixed with a

single push.

also functions as a battery capacity warning lamp.



#### Pipe with beveled end

Cleaning of tight places can be done without nozzle by using the beveled end of pipe as a nozzle.

