

Cordless LED Flashlight DML807



2W Top LED

with light-diffusing reflector and transparent lens



Light diffusing plastic

(color: milky white)




0.5W x 20 LEDs

- for wide and bright illumination
- 360 degree illumination (5 LEDs in a vertical row x 4 sides)


Half brightness

with 10 LEDs (5 LEDs x 2 sides) on



Full brightness

with 20 LEDs (5 LEDs x 4 sides) on



Powered by All Makita LXT 14.4/18V Li-ion batteries

*with Battery fuel gauge



Ring for Strap Strap with hook

DML184) can be

attached.

*BL1860B: 6.0Ah *BL1850B: 5.0Ah *BL1840B: 4.0Ah *BL1830B: 3.0Ah

*BL1820B: 2.0Ah BL1815N: 1.5Ah

Fast Charger DC18RC



*BL1460B: 6.0Ah BL1450B: 5.0Ah BL1440B: 4.0Ah *BL1430B: 3.0Ah BL1415N: 1.5Ah

Battery and charger are

BL1850B


Charger

DC18SD





- can be retracted and stored behind the light head.
- swivels full 360 degrees.





USB output port (Type A, 5V, 2.1A)

with rubber cap to prevent dust and debris from entering



Cordless LED Flashlight

DML807	
Continuous use	Main:
(hours)	20LEDs-11 (BL1850), 6.5 (BL1440),
	10LEDs-23 (BL1850), 13 (BL1440)
	Sub:
	1 X 2W LED -36 (BL1850), 21 (BL1440)
Sub light source (on top side)	Illuminance: 1,900 lx*
	luminous flux: 130 lm
	Type: 1 x 2W LED
Main light source (on bar side)	lluminance (Full brightness): 340lx*
	Illuminance (Half brightness): 310lx*
	Luminous flux (Full brightness): 710lm
	Luminous flux (Half brightness): 340lm
	Type: 20 x 0.5W LED
	Service life: 50,000 or more hours
Dimensions(L x W x H)	414x79x155mm (16-1/4"x3-1/8"x6-1/8")
Net weight	0.72kg (1.6lbs) with BL1415N
	1.0kg (2.3lbs) with BL1850B
Battery and charger are sold separately.	*at 0.5m from the light source

weight according to EPTA-Procedure 01/ver.2.1 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan