



Cordless Kettle  
KT001G



**XGT**  
**40V** LI-ION  
**max**



Water tank capacity  
**0.8 L**

# Hot Water, Anytime Anywhere







**Powered by 40Vmax  
XGT Li-Ion battery**

Battery box is able to hold two XGT series batteries.



**Easy to carry around**



Power supply stand

Kettle can be transferred easily on Power supply stand by holding the carrying handle of the stand.

**Dual layer structure**



Stainless steel interior plus plastic exterior\* provides high heat retention while keeping Kettle surface cool.

\*There is an insulating layer of air between the interior and exterior layers.

**Removable lid**



Removable filter for filtering dust, lime scale and more

Removable for easy water supply and cleaning

**Anti-spill lock button**



Provided to minimize spilling of hot water even if Kettle falls over.

**Easy to read water scale**



**Kettle can be turned on only when grounded.**



Ground sensor

- Auto shut-off after boiling
- Boil-dry protection

Water tank capacity  
**0.8 L**

Boiling time (23°C)  
(approx.)  
**8 min**

Battery BL4040 x2  
capacity of boiling  
water (23°C)  
(approx.)  
**2.2 L**

Power switch



**Portable Power Pack**

**PDC1200**

Powered by 36V-40Vmax built-in battery



**Adapter set (40Vmax)**

Part No. 191N62-4



**Line up**

**LED Flashlight**

ML002G



**Job Site Radio**

MR007G



**Cordless Cooler & Warmer Box**

CW001G



**Accessories**

**Cup**

Part No. KF00000020

Capacity: 240mL



**Charging Time**

| 40V <sup>Li-ion</sup><br>max | Fast Charging |         |
|------------------------------|---------------|---------|
|                              | DC40RA        | DC40RC  |
| *1BL4020 2.0Ah               | 22 min        | 30 min  |
| *1BL4025 2.5Ah               | 28 min        | 38 min  |
| *1BL4040 4.0Ah               | 45 min        | 67 min  |
| *1BL4050F 5.0Ah              | 50 min        | 85 min  |
| *1BL4080F 8.0Ah              | 76 min        | 170 min |

\*1 Recommended battery

**Cordless Kettle**

**KT001G**

|                        |  |
|------------------------|--|
| Water Tank Capacity    | 800 mL   |
| Dimensions (L x W x H) | 233 x 322 x 307 mm<br>(9-1/8 x 12-5/8 x 12-1/8") |
| Net weight             | 2.8 - 5.9 kg (6.2 - 13.0 lbs.)                   |

| Approx amount of hot water for making drinks/foods |             | Boiling time (approx.) of 0.8L water |              |       |       |
|--|-------------|--------------------------------------|--------------|-------|-------|
| Instant/drip coffee                                | 0.2 L       | Starting water temperature           | 10°C         | 23°C  | 40°C  |
| Instant cup soup                                   | 0.15-0.23 L |                                      | Boiling time | 9 min | 8 min |
| Instant cup noodles                                | 0.3-0.5 L   |                                      |              |       |       |

not covered by EPTA-Procedure  
Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202201