

**Accessories**

● Standard equipment ML009GX

**Lamp shade**

Part No. GM00002377 ●  
Model: ML009G



photo: ML009G

- Provides widespread illumination and reduces the glare of LED light.
- Reduces multiple shadows.

**Anti-glare film**

Part No. GM00002376  
Model: ML009G



Part No. GM00002359  
Model: ML005G

Part No. GM00002312  
Model: ML003G




photo: ML005G

When the light source is glaring, attach this film to the lens surface of the light to reduce the glare.

**Tripod**

Part No. GM00002073  
Model: ML005G / ML003G



**Tripod**

Part No. GM00002378  
Model: ML009G / ML005G / ML003G



**Flat bar**

Part No. GM00002379  
Model: ML005G / ML003G



**Vise**

Part No. GM00001396  
Model: ML009G / ML005G / ML003G



photo: ML005G



photo: ML009G

**Continuous run time (approx): hour**

On a single full battery charge

Model	ML009G			
	High	Medium	Low	
<b>40Vmax</b>	BL4020 x2	1.3 h	3.5 h	7.5 h
	BL4025 x2	1.5 h	4.0 h	8.5 h
	BL4040 x2	2.4 h	6.5 h	14 h
	BL4050F x2	3.0 h	8.0 h	17 h
<b>18V</b>	BL1815N x2	0.4 h	1.3 h	2.7 h
	BL1820B x2	0.6 h	1.7 h	3.0 h
	BL1830B x2	0.8 h	2.4 h	4.5 h
	BL1840B x2	1.1 h	3.0 h	6.5 h
	BL1850B x2	1.5 h	4.0 h	8.5 h
	BL1860B x2	1.8 h	5.0 h	10 h

Model	ML005G			ML003G	
	High	Medium	Low	High	Low
<b>40Vmax</b>	BL4020	1.7 h	3.5 h	7.0 h	-
	BL4025	2.2 h	4.5 h	9.5 h	6.0 h
	BL4040	3.5 h	7.5 h	15 h	10 h
	BL4050F	4.0 h	9.5 h	18 h	13 h
	BL4050F	4.0 h	9.5 h	18 h	13 h
<b>18V</b>	BL1815N	0.7 h	1.5 h	3.0 h	2.0 h
	BL1820B	0.9 h	2.0 h	3.5 h	2.9 h
	BL1830B	1.3 h	2.7 h	5.5 h	4.0 h
	BL1840B	1.8 h	3.5 h	7.5 h	5.5 h
	BL1850B	2.3 h	4.5 h	10 h	7.0 h
	BL1860B	2.7 h	5.5 h	12 h	8.5 h

**Charging Time**

Model	Fast Charging		Fast Charging	
	DC40RA	DC40RC	DC18RC	DC18SD
BL4020 2.0Ah	22 min	30 min	15 min	30 min
BL4025 2.5Ah	28 min	38 min	24 min	45 min
BL4040 4.0Ah	45 min	67 min	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	36 min	90 min
BL4080F 8.0Ah	76 min	170 min	45 min	110 min
			55 min	130 min

**Cordless Worklight**

**ML009GX / ML005GX / ML003G**

	ML009G	ML005G	ML003G
Run Time (hrs)	w/ BL4040 x2 Low/Mid/High: 14 / 6.5 / 2.4	w/ BL4040 Low / Mid / High: 15 / 7.5 / 3.5	w/ BL4040 Low / High: 22 / 10
Illuminance (High / Mid / Low)	4,300 / 1,900 / 1,000 lx	2,100 / 1,000 / 500 lx	500 / 200 lx
Luminous Flux	High / Mid / Low: 10,000 / 4,000 / 2,000 lm	High / Mid / Low: 3,600 / 1,800 / 900 lm	High / Low: 1,100 / 450 lm
Lighting Coverage	Front / Sides: 9.7 / 11.4 m	Front / Sides: 6.0 / 6.4 m	Front / Sides: 2.8 / 3.0 m
Dimensions (L x W x H)	w/ Handle in Retracted Position: 248 x 386 x 305 mm (9-3/4 x 15-1/4 x 12")	w/ Handle in Retracted Position: 248 x 309 x 296 mm (9-3/4 x 12-1/8 x 11-5/8")	w/ Handle in Retracted Position: 249 x 298 x 280 mm (9-3/4 x 11-3/4 x 11")
	w/ Handle in Upright Position: 248 x 386 x 430 mm (9-3/4 x 15-1/4 x 17")	w/ Handle in Upright Position: 248 x 309 x 423 mm (9-3/4 x 12-1/8 x 16-5/8")	w/ Handle in Upright Position: 249 x 298 x 386 mm (9-3/4 x 11-3/4 x 15-1/4")
Net weight	6.4 - 9.9 kg (14.1 - 21.8 lbs.)	4.9 - 6.5 kg (10.8 - 14.3 lbs.)	3.7 - 4.7 kg (8.2 - 10.4 lbs.)
Standard Equipment :	Lamp shade (GM00002377)		

Battery and charger sold separately

The weight does not include battery cartridge. Items of standard equipment and specifications may vary by country or area. M4-052023-1



**Cordless Worklight**  
ML009G / ML005G / ML003G



**Cordless Worklight Line up**

ML009G



Luminous Flux  
max  
**10,000 lm**

ML005G



Luminous Flux  
max  
**3,600 lm**

ML003G



Luminous Flux  
max  
**1,100 lm**



Powered by:  
• 40Vmax XGT Li-Ion battery  
• 18V LXT Li-Ion battery  
(two in parallel or one)



**CÔNG TY TNHH MAKITA VIỆT NAM**

Kho 458, Block 16, 19L1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, TP. Hồ Chí Minh, Bình Dương  
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC  
Khu 5, Số 1, Đường Số 6, KCN - DT - DV VSP Bắc Ninh, P. Phú Châu,  
TP. Từ Sơn, T. Bắc Ninh,  
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH HÀ NỘI  
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,  
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH ĐÀ NẴNG  
102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng,  
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH CẦN THƠ  
366 Võ Văn Kiệt, Khu Vực 3, P. An Thủy, Q. Bình Thủy,  
TP. Cần Thơ,  
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH BUƠN MA THUỘT  
88 Lê Đức Thọ, P. Thắng Lợi, TP. Buôn Ma Thuột, T. Đắk Lắk,  
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH HẢI PHÒNG  
Số 01 Lê Duẩn, Di An Hoàng Huy Riverside, P. Thượng Lý,  
Q. Hồng Bàng, TP. Hải Phòng,  
ĐT: 0225 863 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH NHÀ TRANG  
88 Lê Đức Thọ, P. Thắng Lợi, TP. Buôn Ma Thuột, T. Đắk Lắk,  
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG  
CHI NHÁNH HỒ CHÍ MINH  
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,  
ĐT: 0283 821 5191





**ML009G**



**ML005G**




**ML003G**

**ML009G**



**Distance**



Front: about **9.7 m**  
Side: about **11.4 m**

Luminous Flux  
max  
**10,000 lm**

IP65 certified  
dust and  
water  
resistance

**3 brightness settings**


with memory function that remembers the brightness setting last time you power off.



**ML005G**



**Distance**



Front: about **6 m**  
Side: about **6.4 m**

Luminous Flux  
max  
**3,600 lm**

IP65 certified  
dust and  
water  
resistance

**3 brightness settings**


with memory function that remembers the brightness setting last time you power off.



**ML003G**



**Distance**



Front: about **2.8 m**  
Side: about **3 m**

Luminous Flux  
max  
**1,100 lm**

IP65 certified  
dust and  
water  
resistance

**2 brightness settings**

with memory function that remembers the brightness setting last time you power off.



**Battery capacity warning function**



Automatically notifies the user about a decrease in battery capacity with a reduction in illuminance.

**Carrying handle**




Compact design with a short height thanks to the retractable carrying handle

**Angle adjustment**



Knob for free adjustment of light angle enables the light source to rotate from -30° to 210° to a desired angle.

**Switch**



**LED light color: daylight white**



Color temperature: 5,000 K