

Accessories

● Standard equipment ML009GX

● Standard equipment ML005GX

Lamp shade

Part No. GM00002377 ●
Model: ML009G



photo: ML009G

- Provides widespread illumination and reduces the glare of LED light.
- Reduces multiple shadows.

Anti-glare film

Part No. GM00002376
Model: ML009G



Part No. GM00002359
Model: ML005G

Part No. GM00002312
Model: ML003G




photo: ML005G

When the light source is glaring, attach this film to the lens surface of the light to reduce the glare.

Tripod

Part No. GM00002073
Model: ML005G / ML003G



Tripod

Part No. GM00002378
Model: ML009G / ML005G / ML003G



Flat bar

Part No. GM00002379
Model: ML005G / ML003G



Vise

Part No. GM00001396
Model: ML009G / ML005G / ML003G



photo: ML005G



photo: ML009G

Continuous run time (approx): hour

On a single full battery charge

Model	ML009G			
	High	Medium	Low	
40Vmax	BL4020 x2	1.3 h	3.5 h	7.5 h
	BL4025 x2	1.5 h	4.0 h	8.5 h
	BL4040 x2	2.4 h	6.5 h	14 h
	BL4050F x2	3.0 h	8.0 h	17 h
18V	BL1815N x2	0.4 h	1.3 h	2.7 h
	BL1820B x2	0.6 h	1.7 h	3.0 h
	BL1830B x2	0.8 h	2.4 h	4.5 h
	BL1840B x2	1.1 h	3.0 h	6.5 h
	BL1850B x2	1.5 h	4.0 h	8.5 h
	BL1860B x2	1.8 h	5.0 h	10 h

Model	ML005G			ML003G	
	High	Medium	Low	High	Low
40Vmax	BL4020	1.7 h	3.5 h	7.0 h	-
	BL4025	2.2 h	4.5 h	9.5 h	6.0 h
	BL4040	3.5 h	7.5 h	15 h	10 h
	BL4050F	4.0 h	9.5 h	18 h	13 h
	BL4050F	4.0 h	9.5 h	18 h	13 h
18V	BL1815N	0.7 h	1.5 h	3.0 h	2.0 h
	BL1820B	0.9 h	2.0 h	3.5 h	2.9 h
	BL1830B	1.3 h	2.7 h	5.5 h	4.0 h
	BL1840B	1.8 h	3.5 h	7.5 h	5.5 h
	BL1850B	2.3 h	4.5 h	10 h	7.0 h
	BL1860B	2.7 h	5.5 h	12 h	8.5 h

Charging Time

Model	Fast Charging		Fast Charging	
	DC40RA	DC40RC	DC18RC	DC18SD
BL4020 2.0Ah	22 min	30 min	15 min	30 min
BL4025 2.5Ah	28 min	38 min	24 min	45 min
BL4040 4.0Ah	45 min	67 min	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	36 min	90 min
BL4080F 8.0Ah	76 min	170 min	45 min	110 min
			BL1850B 5.0Ah	45 min
			BL1860B 6.0Ah	55 min
			BL1815N 1.5Ah	15 min
			BL1820B 2.0Ah	24 min
			BL1830B 3.0Ah	22 min
			BL1840B 4.0Ah	36 min

Cordless Worklight

ML009G / ML005G / ML003G

	ML009G	ML005G	ML003G
Run Time (hrs)	w/ BL4040 x2 Low/Mid/High: 14 / 6.5 / 2.4	w/ BL4040 Low / Mid / High: 15 / 7.5 / 3.5	w/ BL4040 Low / High: 22 / 10
Illuminance (High / Mid / Low)	4,300 / 1,900 / 1,000 lx	2,100 / 1,000 / 500 lx	500 / 200 lx
Luminous Flux	10,000 / 4,000 / 2,000 lm	3,600 / 1,800 / 900 lm	High / Low: 1,100 / 450 lm
Lighting Coverage	Front / Sides: 9.7 / 11.4 m	Front / Sides: 6.0 / 6.4 m	Front / Sides: 2.8 / 3.0 m
Dimensions (L x W x H)	w/ Handle in Retracted Position: 248 x 386 x 305 mm (9-3/4 x 15-1/4 x 12")	w/ Handle in Retracted Position: 248 x 309 x 296 mm (9-3/4 x 12-1/8 x 11-5/8")	w/ Handle in Retracted Position: 249 x 298 x 280 mm (9-3/4 x 11-3/4 x 11")
	w/ Handle in Upright Position: 248 x 386 x 430 mm (9-3/4 x 15-1/4 x 17")	w/ Handle in Upright Position: 248 x 309 x 423 mm (9-3/4 x 12-1/8 x 16-5/8")	w/ Handle in Upright Position: 249 x 298 x 386 mm (9-3/4 x 11-3/4 x 15-1/4")
Net weight	6.4 - 9.9 kg (14.1 - 21.8 lbs.)	4.9 - 6.5 kg (10.8 - 14.3 lbs.)	3.7 - 4.7 kg (8.2 - 10.4 lbs.)
Standard Equipment :	Lamp shade (GM00002377)	Lamp shade (GM00002358)	

Battery and charger sold separately

The weight does not include battery cartridge. Items of standard equipment and specifications may vary by country or area. (M-052023-1)



Cordless Worklight
ML009G / ML005G / ML003G



Cordless Worklight Line up

ML009G



Luminous Flux
max
10,000 lm

ML005G



Luminous Flux
max
3,600 lm

ML003G



Luminous Flux
max
1,100 lm



Powered by:
• 40Vmax XGT Li-Ion battery
• 18V LXT Li-Ion battery
(two in parallel or one)



CÔNG TY TNHH MAKITA VIỆT NAM

Kho 458, Block 16, 18L1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, TP. Hồ Chí Minh, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG
102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ
366 Võ Văn Kiệt, Khu Vực 5, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUỒN MA THUẬT
88 Lê Đức Thọ, P. Thới Bình, TP. Thuận An, TP. Bình Dương, TP. Biên Hòa.
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG
Số 01 Lê Đức Thọ, Di An Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 863 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHÀ TRANG
88 Lê Đức Thọ, P. Thới Bình, TP. Thuận An, TP. Bình Dương, TP. Biên Hòa.
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191



ML009G



ML005G




ML003G

ML009G



Distance



Front: about **9.7 m**
Side: about **11.4 m**

Luminous Flux max **10,000 lm**

IP65 certified dust and water resistance

3 brightness settings


with memory function that remembers the brightness setting last time you power off.



ML005G



Distance




Front: about **6 m**
Side: about **6.4 m**

Luminous Flux max **3,600 lm**

IP65 certified dust and water resistance

3 brightness settings


with memory function that remembers the brightness setting last time you power off.



ML003G



Distance



Front: about **2.8 m**
Side: about **3 m**

Luminous Flux max **1,100 lm**

IP65 certified dust and water resistance

2 brightness settings

with memory function that remembers the brightness setting last time you power off.



Battery capacity warning function



Automatically notifies the user about a decrease in battery capacity with a reduction in illuminance.

Carrying handle




Compact design with a short height thanks to the retractable carrying handle

Angle adjustment



Knob for free adjustment of light angle enables the light source to rotate from -30° to 210° to a desired angle.

Switch



LED light color: daylight white



Color temperature: 5,000 K