

Accessories • Standard equipment

Guide bar 4 set

Part No. 1910W0-3 😐 Type: 80TXL Length: 100 mm (4")

Gauge: 1.1 mm (0.043)

Thakita

Charging Time

BL1850B 5.0Ah

BL1860B 6.0Ah

The weight may differ depending on the attac

Saw chain 4 set Part No. 1910V6-4 • Type: 80TXL Number of links: 26 Pitch: 0.325" Gauge: 1.1 mm (0.043)





Holster set Part No. 1911R0-4 Storage and carrying of the machine

Net weight



Cordless Pruning Saw

12Vmax	DC10SB	DC10WD
BL1016 1.5Ah	22 min	50 min
BL1021B 2.0Ah	30 min	70 min
BL1041B 4.0Ah	60 min	130 min
	Fast Charging	
	DC18RC	DC18SD
1/8/1/	DCTORC	DCT85D
	Delake	
BL1815N 1.5Ah	15 min	30 min
BL1815N 1.5Ah	15 min	30 min
BL1815N 1.5Ah BL1820B 2.0Ah	15 min 24 min	30 min 45 min

45 min

55 min

Fast Charging

1

DUC101SF01/ DUC101Z01 / UC100DWA01/ UC100DZ01 100 mm (4")

Brake Guide bar length Saw chain Automatic Oiling Chain speed

	DUC101	
Guide bar length	100 mm (4")	
Saw chain	Type: 80TXL	
	Pitch: 0.325"	
	Gauge: 1.1 mm (0.043")	
Chain speed	8.0 m/s (480 m/min) (1,570 FPM)	
Chain oil tank volume	55 mL (1.9 USoz)	
Vibration level	Front: 4.6 m/s ²	
	Rear : 4.0 m/s ²	
Dimensions (L x W x H)	w/o Battery: 357 x 90 x 232 mm	

UC100D 100 mm (4") Type: 80TXL Pitch: 0.325" Gauge: 1.1 mm (0.043") 8.0 m/s (480 m/min) (1,570 FPM) 55 mL (1.9 USoz) Front : 4.8 m/s² Rear : 4.1 m/s² w/o Battery: 350 x 90 x 215 mm
 w/o Battery: 35 / x 90 x 252 mm
 w/o Battery: 35 / x 90 x 215 mm

 w/BL1815N / BL1820B:
 w/ BL1016/BL1021B:

 394 x 90 x 245 mm
 383 x 90 x 220 mm

 w/BL1830B / BL1840B / BL1850B / w/ BL1041B: 398 x 90 x 226 mm
 BL1860B: 408 x 90 x 249 mm
1.5-1.6 kg (3.3-3.5 lbs.)

ent and specifications may vary by country or area. A4-052023-1

1 battery 3.0Ah (BL1830B), charger DC18SD DUC101SE01 UC1010DWA01: 1 battery 2.0Ah (BL1021B), charger DC109U UC100DWA01: 1 battery 2.0Ah (BL1021B), charger DC10WD UC100DZ01: Battery & charger are sold seperately

edure 01/2014, are shown in the table

1.6-2.0 kg (3.5-4.4 lbs.)

Standard Equipment : Sprocket 7 (227947-5), guide bar 100 mm (1910W0-3), guide bar case (413M40-1), saw chain 80TXL (1910V6-4), chain edger 4.0 mm.

CÔNG TY TNHH MAKITA VIỆT NAM KHO 4556, Block 16, 181.12 Buong số 3, KCN VSP I, P. Hos Phu, TP. Thủ Đảu Mặt, Binh Duong DT. 0274 502 8338 - Fair (2074 502 8338 - Website: www.makita.com.un

CHÍ NHÁNH CTÝ TNHH MAKITA VN TAI MIỀN BẮC | TRUNG TÂM DỊCH VỤ KHÁCH HÀNG -Kho 5, Số 1, Đường Số 6, KCN - ĐT - DV VSIP Bắc Ninh, P. Phù Chấn, TP. Từ Son, T. Bắc Ninh. ĐT: 0222 376 5942 _____ Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HÀ NÔI CHI NHÁNH CẦN THƠ 65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội. DT: 0243 202 2585

110 min

130 min

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẰNG 193 Triện Nữ Vượng P. Hậi Chậu 2, Q. Hải Châu, TP. Đà Năm CHI NHÁNH BUÔN MA THUỘT 68 Lê Đức Thọ, P. Tháng lợi, TP. Buôn Ma Thuật, T. Đák Lák. 97: 0262 355 4556 Fax: 0262 355 4557 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG TRUNG TÂM DỊCH VỤ KHÁCH HÀNG 366 Vô Văn Kiệt, Khu Vực 5. P. An Thời, Q. Bình Thủy, TP. Cần Thá. CHI NHÁNH HẢI PHÒNG rside, P. Thương Lý,), Hồng Bàng, TP, Hải Phòng

TRUNG TAM DICH VQ VA CHI NHÁNH NHA TRANG 1ê 3638 dường B6, Khu đô thị Vinh Điểm Trung, Xã Vinh Ngọc 10: 0256 220 0033 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh. ĐT: 0283 821 5191











Net weight

1.5 kg

Battery: BL1021B

Satisfy Professional's Needs













Movable guard

covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.

Lock-off lever accessible from both sides

BL

Work amount

Test conditions: Cut ø50 cedar rod under an optimal pressing load of 20N or less on cutting edge. Saw chain: 80TXL

DUC101 **210** pcs. Battery: BL1830B

UC100D 73 pcs. Battery: BL1021B

Trakita

Guide bar length

100mm



Compact and lightweight **BL motor**





eXtreme Protection Technology

Automatic chain lubrication



minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

Flexible rubber guard for hand



New Tool-less change and tension adjustment of saw chain





• Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain. • This easy-to-operate large lever is designed to be pulled up and turned easily.