

**High Power**  
**Durability**  
**Digital Communication**



**Makita** Cordless Backpack Mist Blower  
**PM001G**

**XGT**  
**40V Li-ion max**



**Accessories** ● Standard equipment

**Diffusion cover**

Part No. 453506-1 ●



**Deflector cover**

Part No. 198248-7 / 198249-5  
*Limited*



**Band 25 set**

Part No. 196733-4



**Charging Time**

	Fast Charging			
	DC40RA	DC40RB	DC40RC	DC40WA
*1BL4050F 5.0Ah	50 min	85 min	260 min	
*1BL4080F 8.0Ah	76 min	170 min	420 min	

**Cordless Backpack Mist Blower**

**PM001G**

Variable Speed	Chemical tank capacity	15.0 L (507 oz)
Electronic 3-Speed	Max air volume	High/Med/Low: 14.3/11.0/9.0 m <sup>3</sup> /min
Constant Speed	Max air velocity	High/Med/Low: 64.0/52.0/42.0 m/s
	Avg. air velocity	High/Med/Low: 53.0/43.0/34.0 m/s
	Vibration level	2.5 or less
	Sound pressure level	84.5 dB (A)
	Sound power level	103.3 dB (A)
	Continuous Use (min.)	w/ BL4080F x2 High: 20
	Dimensions (L x W x H)	w/ Nozzle: 320 x 600 x 690 mm (12-5/8 x 23-5/8 x 27-1/4")
	Net weight	13.2 - 15.7 kg (29.1 - 34.6 lbs.)

Standard Equipment: Nozzle 4.5 (327A93-1), Nozzle 0.5 (327C46-2), diffusion cover (453506-1), wrench 13 (781006-4).

\*1 Recommended battery  
The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area. M4-052023-1

**CÔNG TY TNHH MAKITA VIỆT NAM**

<p>CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC</p> <p>Kho 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.</p> <p>ĐT: 0222 376 5942 Fax: 0222 376 5941</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG</p> <p>102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng.</p> <p>ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 9478</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUƠN MA THUỘT</p> <p>88 Lê Đức Thọ, P. Thắng Mỹ, TP. Buôn Ma Thuột, T. Đắk Lắk.</p> <p>ĐT: 0262 355 4556 Fax: 0262 355 4557</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHÀ TRANG</p> <p>86 Lê Đức Thọ, P. Thắng Mỹ, TP. Thủ Đức, Q. Thủ Đức, TP. Hồ Chí Minh.</p> <p>ĐT: 028 352 0639</p>
<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI</p> <p>65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.</p> <p>ĐT: 0243 202 2585</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ</p> <p>366 Võ Văn Kiệt, Khu Vực 5, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ.</p> <p>ĐT: 0292 389 4358 Fax: 0292 389 4358</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG</p> <p>Số 01 Lê Duẩn, Dã An Hoàng Hai Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.</p> <p>ĐT: 0225 863 1529</p>	<p>TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH</p> <p>Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.</p> <p>ĐT: 0283 821 5191</p>

<p><b>Solution tank capacity</b></p> <p><b>15 L</b></p>	<p><b>Max spray range</b> High spraying speed mode</p> <p><b>14 m</b> (horizontal)</p>	<p><b>Continuous run time</b> on a full battery charge High spraying speed mode</p> <p><b>22 min</b> Battery: BL4080F x2</p>	<p><b>Average particle size</b> High spraying speed mode</p> <p><b>50/150 μm</b> ULV nozzle/Standard nozzle</p>
---	--	--	---







### Switch Interlocking Valve

The opening/closing operation of the solution supply valve is interlocked with the switch trigger to suppress dripping of solution.

### Max spray distance: 14m



### 3 spraying speed modes



- Selectable with the button on control handle
- With mode memory function (In the next operation, the machine will resume operation in the same mode as last time user turn off.)

High spraying speed mode	Long distance spraying allows for outdoor operation.
Medium spraying speed/Low spraying speed mode	For indoor operation or runtime-oriented operation

### ULV compatibility

- Compatible with ULV (Ultra Low Volume) spray for pesticides, etc.
- Only available in High spraying speed mode

Nozzle type	Average particle size
ULV nozzle	50µm
Standard nozzle	150µm

### Powered by 40Vmax XGT Li-Ion battery (two in parallel or one)



### Automatic battery switching

If two batteries are installed and one battery in use has run out of power, the battery system automatically switches to use to the other one.

**Continuous run time**  
on a full battery charge  
High spraying speed mode

**22 min**  
Battery: BL4080F x2

### A variety of front covers

**Diffusion cover**  
You can diffuse the mist by attaching the diffusion cover to the end nozzle



**Deflector set (Option)**  
You can discharge the mist upward or downward by attaching the deflector to the end nozzle



Spray amount adjusting dial



Variable grip



Variable speed trigger



Tank filter port diameter: 0.5mm (max)