



Cordless Pruning Shears UP100D



■ Cordless Pruning Saw

DUC101



Net weight
1.9 kg
Battery: BL1830B



Guide bar length
100 mm

UC100D



Net weight
1.5 kg
Battery: BL1021B



Guide bar length
100 mm



■ Accessories ● Standard equipment

Shear blade U set ●

Part No. 1911W2-5

Replacement upper blade for
Pruning shears



Shear blade L set ●

Part No. 1911W1-7


Replacement lower blade for
Pruning shears



Dresser stone set ●

Part No. 1912E4-1

Dresser stone for Shear blade
sharpening



Holster ●

Part No. 162C23-5



MAKPAC TYPE2

Part No. 821550-0

For smart organization and
easy transportation of power
tools and accessories




■ Charging Time

	Fast Charging	DC10SB	DC10WD
BL1016 1.5Ah		22 min	50 min
BL1021B 2.0Ah		30 min	70 min
BL1041B 4.0Ah		60 min	130 min

Cordless Pruning Shears

UP100DZ



Carrying Case

Capacity	Max cutting: 25 mm (1")
Vibration level	2.5 m/s ² or less
Sound pressure level	70 dB(A) or less
Dimensions (L x W x H)	w/o Battery: 259 x 53 x 98 mm (10-1/4 x 2-1/16 x 3-7/8") w/ BL1016/BL1021B: 285 x 64 x 98 mm (11-1/4 x 2-1/2 x 3-7/8") w/ BL1041B: 308 x 64 x 98 mm (12-1/8 x 2-1/2 x 3-7/8")
Net weight	0.89 - 1.1 kg (2.0 - 2.4 lbs.)
UP100DZ: Battery & charger not include	

Standard Equipment: Shear blade U (1911W2-5), shear blade L (1911W1-7), socket wrench 13 (782212-4), hex wrench 4 (783202-0), hex wrench 2.5 (783208-8), holster (162C23-5), dresser stone (1912E4-1).

MA-052023-1



Max cutting
capacity
Ø25 mm



Lightweight
0.89 kg
with BL1016

Items of standard equipment and specifications may vary by country or area.
The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 456, Block 16, 1BL1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSPP Bắc Ninh, P. Phú Chấn,
TP. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI

65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG

102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng,
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ

366 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy,
TP. Cần Thơ
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUỒN MA THUẬT

88 Lê Đức Thọ, P. Thắng Mỹ, TP. Buôn Ma Thuột, T. Đắk Lắk,
ĐT: 0262 355 4558 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG

Số 01 Lê Duẩn, Di An Hoàng Huy Riverside, P. Thượng Lý,
Q. Hồng Bàng, TP. Hải Phòng,
ĐT: 0225 863 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHÀ TRANG

Lô 36-38 đường B6, Khu đô thị Vĩnh Diễm Trung, Xã Vĩnh Ngọc,
TP. Nhà Trng, T. Khánh Hòa
ĐT: 0258 220 0639

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,
ĐT: 0283 821 5191





Max cutting capacity
Ø25 mm

Lightweight
0.89 kg
with BL1016

12Vmax CXT BL Cordless Pruning Shears

Slim and Lightweight design

The use of BL Coreless motor*¹ allows for reduction in the grip diameter and weight to reduce user's fatigue from pruning.

*¹ BL motor without iron core on which copper coil wire is wound


BL
MOTOR



Blade can be interlocked with the trigger, providing smooth blade movement similar to that of hand pruner.

Two control buttons on the tool body

Main power button and Blade opening angle adjustment button are located side by side on the rear of the grip for easier blade control.



Main power button

Blade opening angle adjustment button

Adjustment of blade opening angle

The opening angle of the shear blades can be set in two levels.

fully open

Ø25 mm



half-open

Ø18 mm



Adjustment of blade overlap when closed



(by pressing and holding Blade opening angle adjustment button for 3 seconds or more when fully closed)



High cutting performance



with BL1021B

Work amount on a full battery charge

When cutting Ø15mm branches of Japanese cypress

about **2,200 pcs**



LED indicator

mounted on the front of the body, allowing the status of the machine to be checked at a glance.



Power on

Blinking: Battery capacity warning (when the capacity is 20% or less)

Solid on: Error indication (No battery capacity/ Thermal protection/ Overload)

External oil port

Lubrication oil can be injected without disassembling the blade.

